

BUILDING PERMIT

PERMIT NO: 2020-0179

PROJECT: SMALL WIRELESS FACILITY (EXISTING POLE)

ISSUE DATE: 10/14/2020 EXPIRATION DATE: 10/14/2021


PROPERTY ADDRESS: 1 ARTHUR AVE R.O.W.

PROPERTY OWNER: VILLAGE OF CLARENDON HILLS

UTILITY POLE OWNER: COMMONWEALTH EDISON

CONTRACTOR: CONCORDIA WIRELESS

A copy of the approved plans must be on site at all times. 24 Hours advance notice required for all building inspections. To schedule an inspection, please call 630-286-5410. Please do not leave any requests on the voicemail as they will not be scheduled until you speak directly with someone in the Community Development Department.



Dan Ungerleider

DAN UNGERLEIDER, AICP
COMMUNITY DEVELOPMENT DIRECTOR



1 N. Prospect Avenue
Clarendon Hills, Illinois 60514
630.286.5410

MEMORANDUM

TO: Permit File – BPA26075

FROM: Dan Ungerleider, Community Development Director


DATE: October 14, 2020

RE: **1 ARTHUR AVENUE - CONCORDIA WIRELESS/VERIZON WIRELESS
SMALL WIRELESS FACILITY ON AN EXISTING COMED UTILITY POLE AT THE NORTHEAST CORNER OF
BURLINGTON AND ARTHUR AVENUES**

The submitted application and plans for the subject facility have been reviewed for compliance with Village Ordinance, and based on the information contained therein:

(x) Permit Application and Plans Submitted to the Village of Clarendon Hills Community Development Department, submitted electronically on 8/7/2020 are **APPROVED**. The Permit will be issued subject to the applicant agreeing to comply with the requirements noted below by signing this memorandum and making it part of the permit documents.

- A. Compliance with the conditions and comments listed in the attached 10/6/2020 report from Village Consultant MSA Municipal Services Associates, Inc., included but not limited to:
 - a. The antennas and equipment shall be painted a neutral color to blend in with the surrounding environment and mitigate visual obstruction.
 - b. Prior to installation, Concordia Wireless provide to the Village of Clarendon Hills Community Development Department a plan for traffic safety for implementation during the installation of the small cell as it is likely that construction vehicles will block portions of Arthur Avenue and Burlington Avenue.
- B. Any work discovered in the field discovered during inspections not indicated on the plans will trigger a stop-work order and require the submittal of revisions to approved plans.
- C. A complete set of the Village approved plans shall always remain on-site during construction/installation.
- D. Required Inspections: Final Inspection by Community Development and Public Works.


Signature (Concordia Wireless) 10/14/2020
Date
Print Name Marisa C. Lewis Green

MSA MUNICIPAL SERVICES ASSOCIATES, INC.

October 6, 2020

Mr. Dan Ungerleider
Director of Community Development
Village of Clarendon Hills
1 North Prospect Avenue
Clarendon Hills, Illinois 60514

Dear Mr. Ungerleider:

At the direction of the Village of Clarendon Hills, Municipal Services Associates, Inc. (MSA) has reviewed the revised plans submitted by Chicago SMSA Limited Partnership d/b/a Verizon Wireless (“Verizon”) for a cellular facility in a right-of-way located on the northeast corner of Arthur Avenue and Burlington Avenue. The address shown on Verizon’s plans indicates that the pole will be installed at Burlington Avenue and Arthur Avenue, however, the actual installation will be located at 1 Arthur Avenue.

The revised project includes the extension of an existing Commonwealth Edison utility pole in order to accommodate a new canister-shaped radome antenna. The pole will also include three (3) antenna/radio units, an antenna mount, two (2) power units, diplexers, a breaker box, new secondary power service wires, a fiber optic cable, and a fiber optic cable interface box. The project also allows for two future combination antenna/radio units, two (2) remote radio units (RRUs), a radio mount, and additional diplexers.

There will be a change to the height of the new pole. With the proposed extension, the utility pole which is presently 29.58' (9.02 meters) above ground level (AGL), will be 34.75' (10.59 meters) AGL. The extension will be 5.166' (1.73 meters) in height. The antenna centerline will be located at 36.58' (11.15 meters). With the antenna, the total height of the pole will be 37.58'(11.46 meters) AGL. Verizon has also included a structural evaluation that is required under the Illinois Small Wireless Facilities Deployment Act (SWFDA).

Existing Facilities: The existing utility pole at this location lack the height to accommodate a small cell antenna, radios, and related equipment. The current pole has a crossbar supported by an angular brace which contains conductors. The crossbar is mounted at 29.58' (9.02 meters) AGL, and the angular brace is mounted at 26.08' (7.95 meters) AGL. A street light is also mounted on the pole. The top of the street light is located at 24.92' (7.60 meters) AGL. An existing neutral electric wire is also located at this elevation.

An existing AT&T communications line is mounted on the pole at 19.67' (6.00 meters) AGL. A guy wire connection is located at 18.92' (5.77 meters) AGL. A Comcast telecommunications cable is also mounted at the same elevation as the guy wire. Other than a Comcast cable riser which extends from grade to a height of 10.42' (3.18 meters) AGL, there are no other existing utilities or appurtenances on the pole.

FCC 2014 Authorization Order “Shot Clock” Period of Review: Concordia Wireless, representative for Verizon Wireless, submitted its application for a permit to the Village on August 7, 2020. A letter sent to Owen Nason, Site Development Specialist for Concordia Wireless was sent by MSA on August 26, 2020, and clarified on September 3, 2020, requesting additional information from Concordia Wireless or Verizon Wireless. The application review period was tolled until September 14, 2020 when Concordia Wireless responded with the remaining information requested by MSA.

The review period for Eligible Facilities Requests such as that proposed by Concordia Wireless and Verizon Wireless is sixty (60) days per the requirements of the FCC Declaratory Order and ninety (90) days per SWFDA. The project application review period was tolled for a period of eleven (11) days. As of the date of this report, forty-seven (47) days have elapsed.

The proposed project does not require a Special Use Permit as the project is not subject to the Village’s Zoning Ordinance due to its location in a public right-of-way. The location of the proposed project in the public right-of-way also classifies it as a Permitted Use under SWFDA (see 50 ILCS 840/15(c)). Other than issuance of required building permits, MSA recommends no additional action from the Village.

Proposed Project Modifications – Radios

Verizon proposes the addition of three (3) Ericsson series 6701 “Streetmacro” radios. These radios actually are dual radio units which operate on two (2) separate transmission and reception bands, and which contain integrated antennas. These radios operate at sub-millimeter wave levels of 27.5 GigaHertz (GHz) to 28.35 GHz. They are considered to be Fifth Generation (5G) radios. The three (3) Series 6701 radio/antenna units will be mounted to the circumference of the pole at 33.16' (10.11 meters) with equal space separation around the pole shaft. These radios have dimensions of 20.1" (.511 meters) in height, 7.9" (.200 meters) in width, and 4.9" (.125 meters) in depth. Each radio weighs 30.8 pounds (14.0 kilograms). A fourth Ericsson Series 4408 Citizens Broadband Radio Service (CBRS) radio will be mounted at 33.16' (10.11 meters). This radio operates in the 3.55 - 3.700 GHz range and is also considered to be a 5G radio. The Series 4408 CBRS radio has dimensions of 8.39" (.213 meters) in height, 7.87" (.200 meters) in width, and 4.13" (.105 meters) in depth. The radio weighs 10.1 pounds (4.59 kilograms).

The project envisions locations for radios to be installed in the future. These radios will be mounted between 13.33' (4.06 meters) and 16.25' (4.95 meters) AGL. The future radios include Ericsson Series 4449 and 8843 radios. These radios operate in the 750-850 MHz, and 1.9 GHz-2.1 GHz bandwidth blocks, respectively. These are 4G/LTE frequencies that are intended to provide 4G/LTE service for those continuing to use 4G phones and other devices. The Series 4449 radios are 17.9" (.455 meters) in height, 13.19" (.335 meters) in width, and 9.45" (.240 meters) in depth, and it weighs 70.55 pounds (32.07 kilograms). The Series 8843 radios are 14.96" (.380 meters) in height, 13.19" (.335 meters) in width, and 10.9" (.277 meters) in depth, and it weighs 71.87 pounds (32.67 kilograms).

Another set of radios to be installed will be Ericsson Series 2205 and 2208 radios that will be housed in two (2) dual radio support boxes to be mounted opposite each other on the pole shaft. Each box will contain a Series 2205 and Series 2208 radio. The radios operate in the 3.55 - 3.700 GHz radios and will provide 5G service. The radio support box housing these radios will be mounted at 13.33' (4.06 meters) AGL. Dimensions for the radio support box are 17.1" (.435 meters) in height, 7.9" (.200 meters) in width, and 5.3" (.134 meters) in depth. The box weighs 21.6 pounds (9.8 kilograms). A power supply unit will be located next to each radio inside its support box. The power supply unit measures 13" (.331 meters) in height, 11.4" (.290 meters) in width, and 3.9" (.099 meters) in depth. Each power supply weighs 22.05 pounds (10.02 kilograms).

A unit of four (4) diplexers, shown on the plans as a dual-band combiner, will be mounted at 16.0' (4.88 meters) AGL and adjacent to the radio support boxes. The diplexer unit has dimensions of 7.32" (.187 meters) in height, 6.14" (.156 meters) in width, and 6.4" (.163 meters) in depth. The diplexer unit weighs 6.9 pounds (3.13 kilograms).

Verizon proposes to install a fiber enclosure box and a breaker box beneath the radio support boxes. Both boxes will be mounted on the pole at 11.0' (3.35 meters) AGL. The dimensions for the fiber enclosure box are 16.0" (.407 meters) in height, 10.0" (.254 meters) in width, and 6.0" (.152 meters) in depth. The fiber enclosure box weighs 12 pounds (5.4 kilograms). The breaker box will contain two (2) 20-Amp circuits and a 60-amp circuit. The breaker box is designed to accommodate up to four (4) additional 15-Amp circuits for future use. The dimensions of the breaker box are 12.6" (.321 meters) in height, 8.9" (.226 meters) in width, and 4.3" (.109 meters) in depth. The breaker box weighs 9.8 pounds (4.45 kilograms).

The following are the points on the pole at which the small cell, street light, and related equipment will be mounted:

<u>Small Cell/Light Component</u>	<u>Prior Installation Height</u>	<u>New Installation Height</u>
Total Height with Antenna:	-----	37.58' (11.46 meters) AGL
Antenna Centerline Height:	-----	36.58' (11.15 meters) AGL
Antenna Base Height:	-----	35.75' (10.90 meters) AGL
Ericsson CBRS Radio	-----	33.16' (10.11 meters) AGL
Ericsson 6701 Radios	-----	33.16' (10.11 meters) AGL
Top of Pole:	29.58' (14.38 meters) AGL	34.75' (10.59 meters) AGL
Street Light Extension Arm and Luminaire:	24.92' (07.60 meters) AGL	24.92' (07.60 meters) AGL
Bottom of Street Light Arm	22.58' (06.88 meters) AGL	22.58' (06.88 meters) AGL
New Fiber Optic Cable	-----	18.92' (05.77 meters) AGL
Fiber "Meet Me" Point	-----	18.92' (05.77 meters) AGL
Four (4) Pack of Diplexers	-----	16.00' (04.88 meters) AGL
Two (2) Power Units	-----	14.00' (04.27 meters) AGL
Ericsson 2205 and 2208 Radios	-----	13.33' (04.06 meters) AGL
Ericsson 4449 and 8843 Radios:	-----	13.33' (04.06 meters) AGL
Bottom of Future Equipment Mount:	-----	13.33' (04.06 meters) AGL
Service Disconnect Breaker Box:	-----	11.00' (03.35 meters) AGL
Fiber Enclosure Box:	-----	11.00' (03.35 meters) AGL

Verizon also proposes a cylindrically-shaped radome antenna manufactured by JMA Wireless. The JMA antenna is 24.0" (.731 meters) in height and 14.6" (.372 meters) in width. The JMA antenna weighs 30.0 pounds (13.6 kilograms).

The JMA "Cantenna," has 18 ports. Four (4) ports support frequencies in the 698-960 MHz block, eight (8) ports support 1.698 -2.69 GHz frequency blocks, four (4) ports support 3.400 - 4.200 GHz frequency blocks, and two (2) ports support 5.150-5.925 GHz frequency blocks. The latter two (2) sets of frequency blocks are used to provide 5G services. The "Cantenna" will support all of the Ericsson radios other than the 6701 Streetmacro series that contain their own antennas.

Grounding: Verizon proposes grounding of its "Cantenna" to a home run ground wire using #4 copper green insulated wire. The CBRS radio, Ericsson 6701 radios, and antenna pipe mounts are also grounded to the home run ground wire by separate #4 copper green insulated wires. As the home run ground wire descends the pole shaft, the diplexer unit, radio support boxes, including the future Ericsson 4449 and 8843 radios, Ericsson 2205 and 2208 radios to be installed initially, along with the fiber enclosure box, and the breaker box will be grounded to the home run ground wire by separate #4 copper green insulated wires.

The home run ground wire will be connected at just below ground level to a #2 tinned solid bare copper conductor wire measuring 12" (.305 meters) in length. The #2 conductor wire will be attached to an 8' (2.44 meters) ground rod buried at a depth of 9' (2.74 meters) below ground level. Verizon's grounding plan was comprehensive and acceptable.

Structural Evaluation: Verizon included a structural evaluation prepared by Concordia Wireless, Inc., of Carol Stream, Illinois on June 23, 2020. The evaluation indicated that the modified utility pole intended to hold the small cell would be sufficient to support Verizon's proposed loads, including those of the mast arm and luminaire. (1).

The pole was subjected to the American National Standards Institute (ANSI) C2-2017 Rule 250B and Rule 250C standards. The ANSI 250B standards utilize criteria of wind speeds of 39.53-MPH with ice of up to 1/2" in thickness (2). The ANSI 250C standards utilize criteria of a wind speed of 90-MPH, a maximum wind speed of 92.91-MPH, and wind pressure of 20.74 pounds per square foot (PSF)(3). Based on the results of the tests, the pole received a combined strength factor rating of 98.3% under heavy load standards under the ANSI 250B and ANSI 250C standards (4)

These ratings indicate that the pole would be adequate to support the radome antenna, combined antenna/radio units, as well as radios mounted on the lower section of the pole, and the fiber enclosure box, breaker box, diplexers, and cabling. It should be noted that higher structure rating percentages indicate less capacity on the pole to accommodate additional antennas, radios, and other equipment, and for such equipment to withstand high wind speeds and loads. The structural evaluation is attached.

Requested Information of Applicant

A letter from Municipal Services Associates, Inc. to Mr. Owen Nason, Site Acquisition Specialist for Concordia Wireless, Inc., originally sent on August 26, 2020, and revised on September 3, 2020, requested additional information from Concordia and Verizon Wireless regarding the following:

- A statement indicating that Verizon will comply with the applicable requirements of 50 ILCS 840/15(d)(6) per the requirements of the Small Wireless Facilities Deployment Act.

(1) Concordia Wireless, Inc., Structural Calculations Modification, Project No. 20171626078, 1 Arthur Avenue, June 23, 2020, at 2 .

(2) *Ibid*, O-Calc Pro Analysis Report, NESC Rule 250B at 1.

(3) *Ibid*, O-Calc Pro Analysis Report, NESC Rule 250C at 1.

(4) *Ibid*, at 2.

- A proposed schedule for the installation and completion of the small wireless facility covered by the application, if approved, in accordance with 50 ILCS 835/15(d)(2)(E).
- Before-and-After photographs of the proposed small wireless facility as it will appear on the utility pole (Application Checklist - Item #2)
- An emergency contingency plan which shall specify the nature of any potential emergencies, including, without limitation, construction and hazardous materials emergencies, and the intended response by the applicant. The intended response shall include notification to the Village and shall promote protection of the safety and convenience of the public (Application Checklist - Item #7). Please indicate if this has already been provided to the Village.
- Documentation establishing that the proposed installation will comply with all ordinances of general application pertaining to installations in the Right-of-Way and Right-of-Way usage. (Application Checklist - Item #14)
- Proof of minimum mandatory insurance, including self-insured retentions. (Application Checklist - Item #15). Please indicate if this has already been provided to the Village.

Mr. Nason responded to the Village's Request for Information on September 14, 2020, and clarified information requested by the Village concerning the proposed electrical contractor. Mr. Nason responded to that request on September 29, 2020. Concordia submitted all of the information required of it for a small cell antenna permit application. No additional information was required, and Concordia and Verizon's submission of requested information as part of the permitting and review process was found to be acceptable. As of October 6, 2020, the application was complete.

Radio Frequency Emissions Safety Compliance: The FCC completely occupies the field as to setting RF safety standards in the United States. The Village is not permitted to set its own standards regardless of whether higher, lower, or even the same as the FCC's standards. The Commission derives its authority under a provision of the National Environmental Policy Act (NEPA) of 1969.

The Commission permits the Village to determine if a proposed wireless project meets the required FCC 47 CFR § 1.1307 et seq. (the "FCC rules") and FCC Office of Engineering and Technology Bulletin 65 ("OET 65") RF safety requirements. The actual standards set by the Commission are found in the FCC Office of Engineering and Technology Bulletin 65, titled "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields."

A website containing the bulletin is at
http://www.fcc.gov/Bureaus/Engineering_Technology/Documents/bulletins/oet65/oet65.pdf.

Under the FCC rules, certain types of wireless projects are deemed to be “categorically excluded,” thus not subject to further RF evaluation under the rules due to identified factors including: whether the antenna supporting structure is a building or is shared to perform some other function, and the lowest portion of the transmitting antenna is at least 10 meters (32.8 feet) above ground.

The proposed project will be operated as a Broadband Personal Communications Services, and that the lowest point of the antenna will be located at 34.58' (10.54 meters), a point that is 1.68' (.512 meters) above the threshold ceiling for regulation of RF exposure of 32.8' (10.00 meters). The proposed project qualifies for categorical exclusion under the FCC rules because the lowest point of each transmitting antenna is greater than 10 meters above ground.

Radio Frequency Interference Issues: The use of panel antennas, small cell antennas, and other forms of wireless telecommunications create a concern that radio frequencies used by cellular and wireless providers might interfere with radio frequencies used for local government public safety and public services communications. Verizon Wireless and other wireless Internet providers may be using a radio frequency spectrum that had been previously used for analog television transmission. Other frequencies formerly used for television transmission will be allocated by the FCC to local governments for public safety uses.

To address this concern, Verizon Wireless provided a statement that it would comply with the requirements of 50 ILCS 840/15(d)(6), a statute within the Illinois Small Wireless Facilities Deployment Act concerning radio frequency interference with public safety responders. Verizon's statement is attached.

Regulatory Summary

The proposed project includes modification of an existing utility pole. The modifications include addition of a radome antenna, three (3) combination antenna/radio units, a Citizens Broadband Radio Service radio unit, four (4) radios reserved for future use and radio power supplies enclosed in two (2) radio support boxes, a unit of four (4) diplexers, a fiber optic cable, fiber optic enclosure box, a breaker box, along with jumper cables, ground wiring, and a ground rod. The proposed project is consistent with the definition of an *Eligible Facilities Request* as stated in 47 CFR §1.6100(b)(3).

Having reviewed the current project plans for this site, MSA's opinions as the Village's technology expert are as follows:

1. The instant project is a "collocation of new transmission equipment" within the meaning of 47 CFR §1.61000(b)(2); and
2. The instant project is a Small Wireless Facilities project as defined by the Federal Communications Commission Declaratory Ruling and Third Report and Order In the Matter of Accelerating Broadband Deployment by Removing Barriers to Infrastructure Investment, Dockets 17-79 and 17-84, Released September 27, 2018. The project is subject to the fees and timetables specified in the Declaratory Ruling, and is also subject to the Spectrum Act at 47 CFR §1.61000. Under the Declaratory Ruling, the Village cannot subject the proposed project to zoning regulations, and must allow the placement of the proposed project.
3. The Illinois Small Wireless Facilities Deployment Act (50 ILCS 840 *et seq.*) (SWFDA) is applicable with respect to its requirements that do not conflict with those of the FCC Declaratory Ruling. To that end, the instant project is consistent with the definition of a Small Wireless Facility under SWFDA, and that its location in a public Right-of-Way exempt it from local zoning regulations and classifies it as a permitted use. The instant project meets the height and volume requirements established by SWFDA and is consistent with design standards established by the Village of Clarendon Hills that are in accordance with requirements set by SWFDA and the FCC Declaratory Order.

Recommendations

Verizon's small cell project located at 1 Arthur Avenue, is the wireless provider's first installation of 5G service in Clarendon Hills. The frequencies that Verizon will use for 5G service will provide substantial increases in wireless capacity and signal delivery speed and throughput.

The proposed modifications to Verizon's small cell project located at 1 Arthur Avenue, are a clear indication of Verizon's intention to provide 5G services to Metra commuters, residences, and vehicular traffic, in Clarendon Hills. Verizon's small cell installation is intended to improve cellular performance in the surrounding area at and near the Metra station, and to provide a wider availability of signal channels and radio frequency spectrums in order to meet ever-expanding demand. None of the proposed antennas and radios operate at frequencies that are considered by the wireless industry or the FCC to be classified as "Millimeter Wave" frequencies, although the Ericsson Series 6701 "Streetmacro" combination antenna/radio units operate at sub-millimeter wave levels of 27.5 GHz to 28.35 GHz.

Mr. Dan Ungerleider

Page 9

MSA recommends that the antennas and equipment be painted a neutral color in order to blend in with the surrounding environment and mitigate visual obstruction. MSA also recommends that if it has not already done so, that Concordia Wireless provide a plan for traffic safety for implementation during the installation of the small cell as it is likely that construction vehicles will block portions of Arthur Avenue and Burlington Avenue.

Should the Village have any questions concerning this report, or if any additional background is needed, please contact me at your first opportunity.

Sincerely,

Stuart Chapman

Stuart Chapman, President
Municipal Services Associates, Inc.

Attachments

cc: Kevin Barr, Village Manager
Brendan McLaughlin, Director of Public Works
Zach Creer, Assistant to the Village Manager
Owen Nason, Concordia Wireless, Representative for Verizon Wireless (ls./att.)



ConcordiaWireless.Com

August 7, 2020

Dan Ungerleider, AICP
Community Development Director
Village of Clarendon Hills
1 North Prospect Avenue
Clarendon Hills, IL 60514

Submitted electronically on 8/7/2020 to dungerleider@clarendonhills.us.

**Re: Verizon / ComEd Pole – Consolidated Small Wireless Facilities Permit
 Applications**

Dear Mr. Ungerleider,

The enclosed package contains documents & plans necessary to reapply to the Village of Clarendon Hills for a Small Wireless Facilities Permit for the site referenced below:

Verizon Location #: 456201
Site Name: Burlington & Arthur SC
Closest Address: 1 Arthur Ave
City: Clarendon Hills
State / Zip code: IL 60514

Verizon Wireless proposes to collocate a small wireless facility on an existing COMED Utility Pole located in the public R.O.W.

Referencing 18-07-20, An Ordinance Amending the Village Code of the Village of Clarendon Hills Relative to the Permitting, Regulation and Deployment of Small Wireless Facilities. Concordia Wireless, Inc. as Agent to Verizon Wireless respectfully submits to the Village of Clarendon Hills for review and granting of a permit package containing the following:

- Village of Clarendon Hills Small Wireless Facilities Permit Application;
- Stamped Construction Drawings. The CDs include the equipment type and model numbers for the antenna and all other wireless equipment associated with the small wireless facility;
- Maps and photographs of the pole proposed for collocation; and,
- Site Specific Structural Analysis (Passing) of the pole proposed for collocation.



The small wireless facility installation takes approximately eight (8) weeks, with construction activities commencing in the beginning of 4Q2020. Construction activities would not be of disturbance to any parties traveling in or about the area. By installing the small wireless facility, it would improve Verizon Wireless' Network performance and contribute to enhancing data transfer speeds by way of the small wireless facility offloading service from other sites.

If you should have questions or comments regarding this submittal, please do not hesitate to give me a call. I can be reached at (224) 239-0831.

Sincerely,

Owen Nason
Site Acquisition Specialist II
C: (224) 239-0831
Concordia Wireless, Inc. as Agent to Verizon Wireless

SMALL WIRELESS FACILITIES PERMIT APPLICATION
APPLICANT INFORMATION

Applicant Name: Owen Nason	Date of Application: 8/6/2020
--------------------------------------	---

Applicant is a: Wireless Provider Representative Other (please specify):
Concordia Wireless as agent for Chicago SMSA limited partnership d/b/a Verizon Wireless

WIRELESS PROVIDER INFORMATION


Wireless Provider Name: Chicago SMSA limited partnership d/b/a Verizon Wireless		
Wireless Provider Address: 1515 Woodfield Rd, Suite 1000		
City: Schaumburg	State: IL	ZIP Code: 60173
Phone: (847) 706-7600	Email: edwardrios1@verizonwireless.com	

CONTACT PERSON FOR THIS PROJECT

Contact Person Name: Owen Nason Concordia Wireless as agent for Chicago SMSA limited partnership d/b/a Verizon Wireless		
Contact Person Address: 361 Randy Road, Ste 101		
City: Carol Stream	State: IL	ZIP Code: 60188
Phone: (224) 239-0831	Email: onason@concordiawireless.com	

PROPOSED SITE LOCATION

Property Address: 1 Arthur Ave, Clarendon Hills, IL 60514		
Closest Intersection (Distance and Direction from): Pole is located on the north side of Burlington Ave - Approx 32 feet northeast from the intersection of Burlington Ave and Arthur Ave	Right of Way <input checked="" type="checkbox"/>	
Zoning District: N/A. Public ROW	Private Property <input type="checkbox"/>	
PIN (if not right-of-way):		



Community Development Department
630-286-5410
www.clarendonhills.us

EXISTING UTILITY POLE/WIRELESS SUPPORT STRUCTURE INFORMATION

Does the Project Involve a New Pole? Yes No

Pole/Structure ID Number:	Height of Pole/Wireless Support Structure (feet): 29'-7"	Pole Color:	Pole Type:
---------------------------	--	-------------	------------

Existing Attachment(s) on Utility Pole/Wireless Support Structure? (e.g., banners, light fixtures) Yes No
If yes, please specify: streetlight

Owner of Pole/Wireless Support Structure: COMED

Name of Pole/Wireless Support Structure Representative: Manny Alonso

Address: Three Lincoln Centre

City: Oakbrook Terrace	State: IL	ZIP Code: 60181
Office Phone: 630-437-2214	Cell Phone:	E-mail: manny.alonso@ComEd.com

NOTE: If the proposed Small Wireless Facility is to be attached to an existing pole owned by an entity other than the Village, the Applicant/Wireless Provider must, with the application, provide legally competent evidence of the consent of the Owner of the Pole to the proposed collocation. Permission Received: Yes No

PROPERTY OWNER INFORMATION (IF PROPERTY NOT VILLAGE-OWNED RIGHT-OF-WAY)

Property Owner Name:

Property Owner Address:

City:	State:	ZIP Code:
-------	--------	-----------

Phone:	Email:
--------	--------

NOTE: If the Small Wireless Facility is to be attached to an existing or new pole or wireless support structure located on property that is not Village-owned right-of-way, the Applicant/Wireless Provider must provide legally competent evidence of the consent of the Private Property Owner to the proposed collocation. Permission Received: Yes No

CONTRACTOR INFORMATION

Name of Contractor:	Type of Contractor:
1. Meade	General and Electric
2.	
3.	

All contractors performing work in the Village must be [licensed/registered] by the Village prior to the issuance of any permit. Please provide appropriate proof of contractor licensing.

OTHER APPROVALS

If any of the Projects are situated within rights-of-way of the Illinois Department of Transportation or of the DuPage County Highway Department, then additional permits from those entities must be obtained and provided as part of this application before a permit may issue.

APPLICATION CHECKLISTS AND REQUIREMENTS

Each Application must be accompanied by the following to be deemed complete:

1. Site specific structural integrity and, for a Village utility pole, make-ready analysis prepared by a structural engineer, as that term is defined in Section 4 of the Structural Engineering Practice Act of 1989, including a certification by the structural engineer that the utility pole or wireless support structure meets the requirements of the applicable code;
2. The location where each proposed small wireless facility, utility pole or wireless support structure would be installed and digital photographs of the location and its immediate surroundings depicting the utility poles or structures on which each proposed small wireless facility would be mounted or location where utility poles or structures would be installed. The photographs shall include a digital photo simulation of the proposed location providing "before and after" views, demonstrating the true visual impact of the proposed wireless facilities on the surrounding environment;
3. Specifications and drawings prepared by a structural engineer, as that term is defined in Section 4 of the Structural Engineering Practice Act of 1989, for each proposed small wireless facility covered by the application as it is proposed to be installed, including a certification by the structural engineer that the drawings and specifications comply with all applicable codes, rules and regulations;
4. The equipment type and model numbers for the antennas and all other equipment associated with the small wireless facility;
5. A proposed schedule for the installation and completion of each small wireless facility, utility pole and wireless support structure covered by the application, if approved;
6. A traffic control plan demonstrating the protective measures and devices that will be employed consistent with the Illinois Manual of Uniform Traffic Control Devices, to prevent injury or damage to persons or property and to minimize disruptions to efficient pedestrian and vehicular traffic. If it is claimed that no traffic control plan is necessary, a statement setting forth the basis for no traffic control;
7. An emergency contingency plan which shall specify the nature of any potential emergencies, including, without limitation, construction and hazardous materials emergencies, and the intended response by the applicant. The intended response shall include notification to the Village and shall promote protection of the safety and convenience of the public;
8. Copies of all licenses, permits and approvals required by or from the Village (i.e. zoning approval, where required), other agencies and units of government with jurisdiction over the design, construction, location and operation of said small wireless facility. The applicant shall maintain such licenses, permits and approvals in full force and effect and provide evidence of renewal or extension thereof when granted;
9. In the event the small wireless facility is proposed to be attached to an existing utility pole or wireless support structure owned by an entity other than the Village, legally competent evidence of the consent of the owner of such pole or wireless support structure to the proposed collocation;
10. In the event the small wireless facility is to be located on private property outside of the right-of-way, legally competent evidence of the consent of the owner of such property to the proposed collocation;
11. Application Fee(s);

APPLICATION CHECKLISTS AND REQUIREMENTS (continued)

12. If the proposed installation includes ground-mounted equipment, compliance with any applicable Village standards, including, where required: a landscape plan showing specific landscape materials, method of fencing, finished color and, if applicable, the method of camouflage or concealment;
13. Copy of existing Master Pole Attachment Agreement with the Village relative to Small Wireless Facilities, if any, if seeking to locate on a Village owned utility pole or wireless support structure;
14. Sufficiently detailed documentation establishing that the proposed installation will comply with all ordinances of general application pertaining to installations in the right-of-way, right-of-way usage and the National Electric Code; and
15. Proof of minimum mandatory insurance, including self-insured retentions.

ATTESTATION, ACKNOWLEDGMENT & SIGNATURE

I attest, to the best of my knowledge and belief, that the information stated in this application and in all supporting plans and documents is true and accurate. In addition, to the best of my knowledge and belief, the proposed collocation of the small wireless facility sought by this application complies with the written design standards established by the Village, and with the various other requirements set forth in the Small Wireless Facilities Deployment Act (P.A. 100-585), Chapter 60 of the Village Code as may be amended from time to time, and other applicable provisions of the Village Code.

This is an application only. Completion of this application does NOT entitle the applicant to commence construction. I, the applicant, agree to conform to all applicable laws of the Village. I also agree that all work performed will be in accordance with the plans and specifications as set forth in the approved permit. I understand that the approval of this application and issuance of a permit does not obviate the need to comply with all applicable laws and ordinances. I agree to hold harmless and indemnify the Village for any claim against the Village as the result of any act of commission or omission by or on behalf of the undersigned, his/her agent, principle, contractor, subcontractor or supplier. I, the undersigned, am the duly authorized and contracted representative of the applying entity/owner of the small wireless facility.

Signature of Applicant: 	Date: 8/17/2020
Printed Name of Applicant: Owen Nason	Title: Site Acquisition Specialist II
State of <u>ILLINOIS</u>	County of <u>DU PAGE</u>
Signed and sworn (or affirmed) to before me on <u>7th day of July 2020</u> by <u>Owen Nason</u> .	
Signature of Notary Public: <u>Vafa Askarova</u>	<div style="border: 1px solid black; padding: 5px; text-align: center;"> VAFA ASKAROVA Official Seal Notary Public - State of Illinois My Commission Expires Jan 3, 2023 </div>

****FOR ADMINISTRATIVE USE ONLY****

Date Application was submitted: AUGUST 21, 2020

Application Is: Complete / Incomplete as of _____

If incomplete, date the Applicant was notified: _____

Missing documents or information:

Date Application was approved / denied _____

See 10/14/2020 memorandum to file from Community Development Director
 Dan Ungerleider for detailed review and conditions of permit issuance.

VILLAGE OF CLARENDON HILLS

APPROVED

This approval does not relieve applicant from responsibility of conforming with provisions of Building and Zoning Ordinances

CHICAGO SMSA

limited partnership
d/b/a VERIZON WIRELESS

Project Number
20171626078
Location Number
456201

Site Name
BURLINGTON AND ARTHUR SC

SCOPE OF WORK

(1) FUTURE LESSEE RADIOS W/INTEGRATED ANTENNAS
(1) FUTURE ERICSSON RADIO 4449
(1) FUTURE ERICSSON RADIO 8843
(1) FUTURE CBR5 RADIO
MOUNTED ON A 29'-7" HIGH EXISTING UTILITY POLE
POWER: OVERHEAD DROP
FIBER: OVERHEAD DROP

DRIVING DIRECTIONS


DRIVING DIRECTIONS FROM 1515 WOODFIELD RD, SCHAUMBURG

1. HEAD NORTH 0.2 MI
2. TURN RIGHT onto WOODFIELD RD 0.2 MI
3. TURN LEFT onto E HIGGINS RD 0.3 MI
4. USE THE RIGHT 2 LANES TO TURN RIGHT onto FRONTAGE RD 0.1 MI
5. USE THE LEFT 2 LANES TO TAKE THE INTERSTATE 290 E RAMP TO CHICAGO 0.4 MI
6. KEEP RIGHT AT THE FORK TO STAY ON I-290 E. FOLLOW SIGNS FOR CHICAGO 4.4 MI
7. TAKE EXIT 10A TOWARD IL-83 S 0.4 MI
8. MERGE onto IL-83 S 7.3 MI
9. TAKE THE US 340/GENEVA EXIT 0.3 MI
10. TURN RIGHT onto US-34/W. OGDEN AVE 0.5 MI
11. TURN LEFT onto WOODSTOCK AVE 0.5 MI
12. TURN RIGHT onto E CHICAGO AVE 0.95 FT
13. TURN LEFT onto ARTHUR AVE 0.5 MI

DESTINATION WILL BE ON THE LEFT

TOTAL TRAVEL ESTIMATE: 20.3 MI / 38 MIN

AERIAL MAP



Sheet Index

NO.	Sheet Description	Drawn by: MC	Checked by: GMS	Approved by: GMS
SP-1	GENERAL NOTES AND SPECIFICATIONS			
LP-1	MAP & EXHIBIT PHOTOS			
A-0	SITE PLAN			
A-1	EXISTING POLE/WIPOPOSED EQUIPMENT ELEVATION			
A-2	EQUIPMENT DIAGRAM			
A-3	FIBER CONNECTION DETAILS			
A-4	RF SHEETS			
A-5	IEC SHEET			
A-6	EQUIPMENT SPECIFICATIONS			
A-7	EQUIPMENT SPECIFICATIONS			
A-8	EQUIPMENT SPECIFICATIONS			
A-9	EQUIPMENT SPECIFICATIONS			
A-10	EQUIPMENT MOUNTING DETAILS			
A-11	ANTENNA MOUNT & POLE EXTENSION DETAILS			
A-12	EQUIPMENT MOUNTING DETAILS			
E-1	ELECTRICAL MOUNTING & DETAILS			
G-1	GROUNDING DETAILS			

Site Address

1 ARTHUR AVE

CLARENDON HILLS, IL 60514

MODIFICATION

Site Name
BURLINGTON AND ARTHUR SC

SCOPE OF WORK

(1) FUTURE LESSEE RADIOS W/INTEGRATED ANTENNAS
(1) FUTURE ERICSSON RADIO 4449
(1) FUTURE ERICSSON RADIO 8843
(1) FUTURE CBR5 RADIO
MOUNTED ON A 29'-7" HIGH EXISTING UTILITY POLE
POWER: OVERHEAD DROP
FIBER: OVERHEAD DROP

DRIVING DIRECTIONS

DRIVING DIRECTIONS FROM 1515 WOODFIELD RD, SCHAUMBURG

1. HEAD NORTH 0.2 MI
2. TURN RIGHT onto WOODFIELD RD 0.2 MI
3. TURN LEFT onto E HIGGINS RD 0.3 MI
4. USE THE RIGHT 2 LANES TO TURN RIGHT onto FRONTAGE RD 0.1 MI
5. USE THE LEFT 2 LANES TO TAKE THE INTERSTATE 290 E RAMP TO CHICAGO 0.4 MI
6. KEEP RIGHT AT THE FORK TO STAY ON I-290 E. FOLLOW SIGNS FOR CHICAGO 4.4 MI
7. TAKE EXIT 10A TOWARD IL-83 S 0.4 MI
8. MERGE onto IL-83 S 7.3 MI
9. TAKE THE US 340/GENEVA EXIT 0.3 MI
10. TURN RIGHT onto US-34/W. OGDEN AVE 0.5 MI
11. TURN LEFT onto WOODSTOCK AVE 0.5 MI
12. TURN RIGHT onto E CHICAGO AVE 0.95 FT
13. TURN LEFT onto ARTHUR AVE 0.5 MI

DESTINATION WILL BE ON THE LEFT

TOTAL TRAVEL ESTIMATE: 20.3 MI / 38 MIN

PROJECT LICENSE

APPLICANT: CHICAGO SMSA LIMITED PARTNERSHIP d/b/a VERIZON WIRELESS 1515 WOODFIELD ROAD SUITE 1000 SCHAUMBURG, IL 60173 SITE ACQUISITION: CONCORDIA WIRELESS, INC. 381 RANDY ROAD UNIT 101 CAROL STREAM, IL 60113 CONTACT: MARIA GREEN PHONE: (847) 381-0201 POLE OWNER: COMED LICENSED STRUCTURAL ENGINEER: HABIB FARROUDIN ET. CHARLES 23777 EXPIRES: 11/30/2020

STATE OF ILLINOIS
LICENSED STRUCTURAL ENGINEER
HABIB FARROUDIN
ET. CHARLES
23777
EXPIRES: 11/30/2020
SIGNED: 06/22/20

PROJECT INFORMATION

PROJECT #: 20171626078
LOCATION: # 456201
BURLINGTON AND ARTHUR SC
1 ARTHUR AVE
CLARENDON HILLS, IL 60514
SHEET TITLE: TITLE SHEET
SHEET NUMBER: T-1
CODES:
1. INTERNATIONAL BUILDING CODE 2015
2. NATIONAL ELECTRICAL CODE (NEC) (AC) 2018
3. AMERICAN INSTITUTE OF STEEL CONSTRUCTION (AISC) MANUAL OF STEEL CONSTRUCTION
5. TELECOMMUNICATIONS INDUSTRY ASSOCIATION (TIA) 22-2-G, STRUCTURAL STANDARDS FOR STEEL TOWER AND ANTENNA SUPPORTING STRUCTURES
6. TIA 607, COMMERCIAL BUILDING GROUNDING AND TERRAIN ENGINEERING
7. ANSI C3007 (NEC) 2007
8. COMED TPA SPEC (C-7238)

PROFESSIONAL LICENSURE

STATE OF ILLINOIS
LICENSED STRUCTURAL ENGINEER
HABIB FARROUDIN
ET. CHARLES
23777
EXPIRES: 11/30/2020
SIGNED: 06/22/20

CHICAGO

SMSA

limited partnership
db/a VERIZON WIRELESS



1 PROJECT SYMBOLS

1 SCALE: 1'ITS

1. REPRESENTATIVES OF THE OWNER MUST BE NOTIFIED AT LEAST TWO FULL DAYS PRIOR TO COMMENCEMENT OF CONSTRUCTION.
2. DO NOT EXCAVATE OR DISTURB BEYOND THE PROPERTY LINES OR LEASE LINES.
3. DO NOT SCALE BUILDING DIMENSIONS FROM DRAWINGS.
4. ANY DRAWINGS AND FIELD CONDITIONS, CONDITIONS, AND THEIR DIMENSIONS SHOWN ON PLANS HAVE BEEN PLOTTED FROM ORIGINAL AS-BUILT DRAWINGS AND ARE NOT TO BE USED AS A BASIS FOR CONSTRUCTION. THE CONTRACTOR SHALL RETURN DRAWINGS TO THE OWNER OR TO THE ENGINEER FOR COMPLETION OF WORK SIZE, LOCATION AND ACCURACY OF ANY DRAWINGS AND CONDITIONS AS SHOWN ON THE PLANS. THE CONTRACTOR SHALL NOT USE ANY DRAWINGS OR CONDITIONS AS A BASIS FOR CONSTRUCTION.
5. ALL EXISTING UTILITIES, FACILITIES, CONDITIONS, AND THEIR DIMENSIONS SHOWN ON PLANS HAVE BEEN PLOTTED FROM ORIGINAL AS-BUILT DRAWINGS AND ARE NOT TO BE USED AS A BASIS FOR CONSTRUCTION. THE CONTRACTOR SHALL NOT USE ANY DRAWINGS OR CONDITIONS AS A BASIS FOR CONSTRUCTION.
6. CONTRACTOR SHALL KEEP ALL EXISTING UTILITIES BOTH HORIZONTALLY AND VERTICALLY PRIOR TO START OF CONSTRUCTION. THE CONTRACTOR SHALL NOT DISTURB ANY EXISTING UTILITIES, FACILITIES, CONDITIONS, AND THEIR DIMENSIONS SHOWN ON PLANS. THE CONTRACTOR SHALL NOT USE ANY DRAWINGS OR CONDITIONS AS A BASIS FOR CONSTRUCTION.
7. ALL NEW AND EXISTING UTILITIES ON SITE AND IN AREAS TO BE DISTURBED BY CONSTRUCTION SHALL BE ADJUSTED TO FINISH ELEVATIONS PRIOR TO FINISHING EARTHWORK.
8. THE BUILDING DEPARTMENT ISSUING THE BUILDING PERMIT SHALL BE NOTIFIED AT LEAST TWO WORKING DAYS PRIOR TO THE COMMENCEMENT OF WORK AS STATED BY THE CODE OR LOCAL OFFICE OF BUILDING INSPECTION.
9. GRADING OF THE SITE WORK AREA IS TO BE DERTINED AND CONTINUOUS IN ELEVATION. THE CONTRACTOR IS TO ENSURE THAT THE GRAVING UNITS ARE PROPERLY LAID BACK OR RADED IN ACCORDANCE WITH CORRECT OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA) REQUIREMENTS.
10. ALL EXCAVATION FOR THE INSTALLATION OF FOUNDATIONS, UTILITIES, ETC. SHALL BE PERFORMED IN ACCORDANCE WITH CORRECT OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA) REQUIREMENTS.
11. STRUCTURAL SUPPORTING PAVEMENTS SHALL BE COMPACTED TO 100% OF MAXIMUM STANDARD PRACTICE ONE DAY.
12. NEW GRADES AND IN BUILDING AND DRIVEWAY AREAS TO BE ADVISED OF TRACTOR DENSITY.

2 PROJECT ABBREVIATIONS

2 SCALE: 1'NTS

13. ALL PILES SHALL BE PLACED IN INFORMED LOTS. THE WIDTH THICKNESS SHOULD NOT EXCEED 12 INCHES. THE PILES CAN BE PROPERLY COMPACTED THROUGHOUT ITS ENTIRE DEPTH WITH THE EQUIPMENT AVAILABLE.
14. ANY TILLS PLACED ON EXISTING LAWNS THAT ARE TO BE PLACED BY A VERTICALLY CHAKED DRAVE.
15. THE GRADES WITHIN THE FEEDING AREA ARE TO BE ACHIEVED BY COMPACTING THE GRADE WITH A 6' ROLLER. THE GRADE IS TO BE PLACED ON A 6' ROLLER FOR WED SUPPRESSION, THEN ACHIEVING FINISH GRADE BY ADDING 6" OF 3/4 CRUSHED STONE. NO PILES.
16. CONTRACTOR SHALL CLEAN ENTIRE SITE AFTER CONSTRUCTION SO THAT NO WASTERS, TRASH, WEEPS, BRUSH OR ANY OTHER DEBRIS WILL REMAIN. ALL MATERIALS COLLECTED DURING CLEANING OPERATIONS SHALL BE DISPOSED OF ON-SITE.
17. ALL TREES AND SHRUBS WHICH ARE NOT IN DIRECT CONFLICT WITH THE IMPROVEMENTS SHALL BE PROTECTED.
18. SOIL TO THE PUBLIC & PRIVATE LOCATE SERVICE IN ORDER TO LOCATE AND PROTECT ANY AND ALL SURFACE UTILITIES. NO NOTIFICATION OR RELEASE OF THESE PLANS OR ANY BELOW-GROUND UTILITIES.
19. THREE PANS AND A LOT CONTAINING REVEAL AND SUBSTRUCTURES. OC IS RESPONSIBLE OF LOCATING AND PROTECTING ALL UTILITIES DURING CONSTRUCTION.

3 GENERAL NOTES

3 SCALE: 1'NTS

PROJECT # 2017162078
LOCATION # 456201
BURLINGTON AND ARTHUR SC
1 ARTHUR AVE
CLARENCE HILLS, IL 60514

SHEET TITLE
GENERAL NOTES
SHEET NUMBER
SP-1

**CHICAGO
SMSA**

limited partnership
d/b/a VERIZON WIRELESS

CONCORDIA LTD
A PROFESSIONAL DESIGN FIRM
LICENSE #400-044-A

CONCORDIA WIRELESS, INC.

381 RANDY ROAD

UNIT 101

CAROL STREAM, IL 60188

MAIN: (847) 985-4001




DRAWN BY: MK

CHECKED BY: GMS

APPROVED BY: GMS

CHECKED BY: RH



1 AERIAL MAP
SCALE: N.T.S.



PROPOSED LOCATION
OF NEW LESSEE SMALL
CELL INSTALLATION


2 DUPAGE COUNTY GIS MAP
SCALE: N.T.S.

3 EXHIBIT PHOTOS OF UTILITY POLE
SCALE: N.T.S.

PROJECT #: 20171626078
LOCATION #: 4562011
BURLINGTON AND ARTHUR SC
1 ARTHUR AVE
CLARENDON HILLS, IL 60514

SHEET TITLE:
MAPS & EXHIBIT
PHOTOS

SHEET NUMBER:
LP-1



CHICAGO
SMSA

limited partnership
d/b/a VERIZON WIRELESS


CONCORDIA LTD. DESIGN FIRM
LICENSED #323-911 D.A.
CONCORDIA WIRELESS, INC.



381 RANDY ROAD
UNIT 101
CAROL STREAM, IL 60163
HVN: (630) 961-0801

DRAWN BY: MK
CHECKED BY: CMS
APPROVED BY: GMS


CHECKED BY: RH
APPROVED BY: GMS



PROJECT # 20171626078
LOCATION # 456201
BURLINGTON AND ARTHUR SC
1 ARTHUR AVE
CLARENDON HILLS, IL 60514

TRAFFIC CONTROL PLAN
SHEET NUMBER:
A-1

CHICAGO SMSA limited partnership dba VERIZON WIRELESS			
		CONCORDIA LTD. A PROFESSIONAL DESIGN FIRM LICENSE # 5323-011-D.O.A. 161 RANDY ROAD UNIT 101 CAROL STREAM IL 60118 MAIN: (647) 891-0801	
		DRAWN BY: MK CHECKED BY: RH APPROVED BY: GMS	DRAWN BY: MK CHECKED BY: RH APPROVED BY: GMS
		PROJECT # 20171626078 LOCATION # 465201 BURLINGTON, 1 ARTHUR AVE CLARENDON HILLS, IL 60514	
		SHEET TITLE: SCHEMATIC DIAGRAM SHEET NUMBER: A-3A	



LEGEND

- * GC TO REFER TO RFDS SHEET FOR FINAL EQUIPMENT CONFIGURATION
- ** CCAJ: JUMPER LENGTH LIES THAN 6 IN. ENTHC: CCA TO PROVIDE ONLY 1 LINE IDENTITY TAG NEAR RRU CONNECTOR.
- ◆ INDICATES LOCATION OF TAGS

TYP. LINE IDENTITY TAG

700 RX/TX0

OC TO PROVIDE LINE IDENTITY TAG NEAR CONNECTORS; SEE DETAIL 1 THIS SHEET FOR MORE INFO (TYP. OF 1 PER RRU JUMPER)

GO TO TERMINATE & CAP ALL UNUSED PORTS (TYP.)

NOTES:

* GC TO REFER TO RFDS SHEET FOR FINAL EQUIPMENT CONFIGURATION

** CCAJ: JUMPER LENGTH LIES THAN 6 IN. ENTHC: CCA TO PROVIDE ONLY 1 LINE IDENTITY TAG NEAR RRU CONNECTOR.

◆ INDICATES LOCATION OF TAGS

RF EMISSIONS REPORT REQUIRED

YES NO DATE OF REPORT:

RF CONFIG: TEMPLATE 4

LINE IDENTITY	TAG COLOR	BLACK										
TECHNOLOGY	700	700	850	850	PCS	PCS	PCS	AWS	AWS	AWS	AWS	AWS
RX/TX0	RX/TX0	RX/TX1	RX/TX0	RX/TX1	RX/TX0	RX/TX1	RX/TX0	RX/TX1	RX/TX0	RX/TX1	RX/TX0	RX/TX1


1 LINE IDENTITY TAG SCHEDULE

LINE IDENTITY	TAG COLOR	BLACK										
TECHNOLOGY	700	700	850	850	PCS	PCS	PCS	AWS	AWS	AWS	AWS	AWS
RX/TX0	RX/TX0	RX/TX1	RX/TX0	RX/TX1	RX/TX0	RX/TX1	RX/TX0	RX/TX1	RX/TX0	RX/TX1	RX/TX0	RX/TX1

2 NEW EQUIPMENT SCHEMATIC DIAGRAM

SCALE: N.T.S.

A-3A



Service Info


2.4 GHz									
Sector									
Antennas									
Cell Block B 10									
Antenna Model									
Antenna Name									
Antenna Certificate#1									
Mechanical Design#1									
Electrical Design#1									
The Height									
Transmitter Power									
TRX Name									
TRX Model									
TRX Serial									
Number of Txs in Lines									
Position									
Source									
Sector Comments									


Cells/Cells per Antenna

Sector	Antenna Model	Antenna Model Antenna	Antenna Model Antenna	Tip Height	Antennas (TIN)	Electrical Gain	Mechanical Gain	TR	Baseband		2.4 GHz	3.5 GHz	36 GHz
									Cellphone	Power			
0102	F100-502N	12' 00" H11 1/2	11	14.0	125	0	C	24.6dB	700	650	1200	2100	28 GHz
0101	F100-502N	12' 00" H11 1/2	34	14.3	9	0	E	25.0dB	125.5	160.25	160.25	160.25	160.25
0103	F100-502N	12' 00" H11 1/2	34	14.3	243	0	C	26.6dB	700	650	1200	2100	28 GHz

PROJECT #: 20171626078
LOCATION # 465201
BURLINGTON AND ARTHUR SC
1 ARTHUR AVE
CLARENDON HILLS, IL 60514

SHEET TITLE:
RFDS SHEETS
SHEET NUMBER:
A-3D






NOTE: * GO TO REFER TO RFD SHEET FOR FINAL EQUIPMENT CONFIGURATION AND VERIFY WITH LESSEE/PM PRIOR TO CONSTRUCTION REGARDING EQUIPMENT AVAILABILITY

**CHICAGO
SMSA**
limited partnership
d/b/a VERIZON WIRELESS


CONCORDIA LTD
A PROFESSIONAL CORPORATION
LICENSE #3525411-D.O.A.
CONCORDIA WIRELESS, INC.
361 RANDY ROAD
UNITED STREAM, IL 60143
MAIN: (847) 891-4801

DRAWN BY: MK
CHECKED BY: GMS
APPROVED BY: GMS

DRAWN BY: MK
CHECKED BY: RH
APPROVED BY: GMS



Port	Description
A	Optical Cable 1
B	Optical Cable 2
C	Optical Cable 3
D	Optical Cable 4
E	Optical Indicators
F	External Alarm and Fan Control
G	48V DC Power Supply
H	Grounding Point




Specifications


Depth	5.67"
Height	23.94"
Width	11.81"
Weight	30.86 lbs
Frequency	27.5-28.3GHz
Operating	400MHz
Bandwidth	550Bm
ERP (total)	600Bm
Cooling	Passive
Installation Type	Pole/Wall
Power	Max: 205W
Consumption	AC
Power	2x10G CPRI
CPRI/TN Ports	

1 ERICSSON - AIR 5121 RADIO W/ANTENNA *
2 N.T.S.

ERICSSON - AIR 5331 RADIO W/ANTENNA *



Port	Description
A	Grounding Point
B	100-250V AC Power Supply
C	External Alarm Interface
D	Optical Indicators
E	Optical Cable 1
F	Optical Cable 2





Port	Description
A	Optical Cable 1
B	Optical Cable 2
C	Optical Cable 3
D	Optical Cable 4
E	Optical Indicators
F	External Alarm and Fan Control
G	48V DC Power Supply
H	Grounding Point

SHEET TITLE:
EQUIPMENT
SPECIFICATIONS
SHEET NUMBER:
A-4C

NOTE:
* GO TO REFER TO RFD'S SHEET FOR FINAL EQUIPMENT CONFIGURATION AND VERIFY WITH LESSOR/PMI PRIOR TO CONSTRUCTION REGARDING EQUIPMENT AVAILABILITY

Streetmacro 6701

Connection Interfaces



Dimensions, Weight, and Color

Description	Value
Frequency	B261 (27.5-28.35 GHz)
Number of carriers	511 mm
Config mode 2:	289 mm
Config mode 1:	128 mm
Config mode 1:	14 kg
Color	Gray
Reference number:	MC5 S 1002-B

Technical Data

Description	Value
Frequency	B261 (27.5-28.35 GHz)
Config mode 2:	Up to 8
Config mode 1:	Up to 16
Operating bandwidth	Config mode 2: 800 MHz Config mode 1: 1600 MHz 50MHz, 100 MHz
Component carrier bandwidth (ERP ⁽¹⁾)	Config mode 2: 53 dBm per RF beam in boresight, -56 dBm per radio Config mode 1: 47 dBm per RF beam in boresight, -53 dBm per radio Config mode 2: -49 dBm Config mode 1: -36 dBm
EIRP(FRS, 5.8GHz)	(1) The Max Tx Power can be configured to 10 dB lower than the stated EIRP without render performance being payed. If the Max Tx Power is configured lower than the given power limit, here, significant performance degradation will occur.

CHICAGO SMSA limited partnership dba VERIZON WIRELESS	
CONCORDIA LTD. DESIGN FIRM LICENSE # 4323412 DSA CONCORDIA WIRELESS, INC. 381 RANDY ROAD UNIT 101 CAROL STREAM, IL 60188 TEL: (847) 861-4601	
DRAWN BY: MK CHECKED BY: OMS APPROVED BY: GMS	CHECKED BY: RH APPROVED BY: GMS

Position	Marking	Connector	Description	Optical Indicator ⁽²⁾
A	!	-	Fault	Optical indicator, red
	✓	-	Optical indicator, red	Yes
	✗	-	Optical indicator, green	Yes
	❖	-	Maintenance	Optical indicator, blue
	❖	-	For information on the maintenance button, see Indicators, Buttons, and Switches.	Indicators, Buttons, and Switches.
	❖	-	Status	Optical indicator, yellow
	❖	-	Fan anti fault	Optical indicator, yellow
B	-	-	Maintenance button	Yes
	-	-	For information on the maintenance button, see Indicators, Buttons, and Switches.	Indicators, Buttons, and Switches.
C	SYNC	RJ-45	Synchronization interface	Yes
D	ALARM/EC	RJ-45	EC light and two external alarm inputs	Yes
E	TN A ⁽³⁾	RJ-45	100 Mbps/1 Gbps Ethernet transport interface	Yes
	-	-	External interface for site LAN, electrical	External interface for site LAN, electrical
F	LMT	RJ-45	LMT A interface ⁽⁴⁾	Yes
	-	-	LMT B interface ⁽⁵⁾	TN
	-	-	Sync test interface ⁽⁶⁾	1 Gbps/10 Gbps Ethernet transport interface
	-	-	Internal and external interfaces	External interface, optical
G, H	TN/TDL B	SFP ⁽⁸⁾		
	TN/TDL C			
I, J	Gr-A			
	Gr-B			
K	100-250V -	100-250V AC power connector	100-250V AC power	Yes
L	✓	Dual lug with two M6 screws	GNSS antenna cable connector	GNSS antenna cable connector
M	✓		Ground	

- (1) For more information on optical indicators, see Indicators, Buttons, and Switches.
- (2) Supports synchronization over the transport network.
- (3) RS-232 interface. Accessed with the LMT splitter cable.
- (4) For more information about the LMT interfaces, see Connect Client.
- (5) 100 Mbps electrical Ethernet interface.
- (6) Compliant with IEEE 802.3 phase synchronization measurement interface. Accessed within antenna.
- (7) For more information about the sync test interface, see MC5 S 1002-B.
- (8) SFP⁽⁹⁾ is needed for transmission rates above 2.5 Gbps.
- (9) On the GNSS receiver unit.

SHEET TITLE	EQUIPMENT SPECIFICATIONS
SHEET NUMBER	A-4D

1 ERICSSON - STREETMACRO 6701 RADIO W/ANTENNA

1

**CHICAGO
SMSA**
**limited partnership
d/b/a VERIZON WIRELESS**

**CONCORDIA LTD.
A PROFESSIONAL DESIGN FIRM
LICENSE # 3323411-D.B.A.
CONCORDIA WIRELESS, INC.**

**361 RANDY ROAD
UNIT 101
CAROL STREAM IL 60163
MAIN: 640-981-2001**
DRAWN BY: MR. CHECKED BY: GMS
APPROVED BY: RH

Cat	Item	Model	Dimensions (inches)			Volume	Area	Weight	Number (per site)	Total Volume	Total Weight	Note
			H	W	D							
Antennas	Amphenol	QXW-532x631x5F-EDIN	23.2	12	7.1	1.14	1.9	0.00	11	0	0.00	0.00
	Amphenol	CUUX065X065Px20	24	12.1	7	2.33	n/a	28.70	0	0.00	0.00	0.00
	Amphenol	CW7070X06100-1	24	14.6 (Dia)		2.33	n/a	22.00	0	0.00	0.00	0.00
	Kathrein	840-10794	24.6	16 (Dia)		2.86	n/a	39.90	0	0.00	0.00	0.00
	Kathrein	840-10510	24	16 (Dia)		2.79	n/a	45.00	0	0.00	0.00	0.00
	Kathrein	840-10515	24	16 (Dia)		2.79	n/a	50.00	0	0.00	0.00	0.00
	JMA	CX180M125-1C	24	14.6 (Dia)		2.33	n/a	30.00	1	2.33	Future	
	JMA	CK00M125-1C	27.5	14 (Dia)		2.45	n/a	38.60	0	0.00	0.00	0.00
Radio/ Antenna *	JMA	XGU-165	12	12.6	5.6	0.49	1.1	10.80	0	0.00	0.00	0.00
	Ericsson	AIR 5331 (***)	23.62	11.93	6.26	1.02	2.0	30.86	0	0.00	0.00	0.00
	Ericsson	AIR 5121 (***)	23.94	11.81	5.67	0.93	2.0	30.86	0	0.00	0.00	0.00
	Ericsson	STREETMACRO 6701 (***)	23.20	8.10	5.10	0.51	1.2	31.00	3	1.52	93.00	New
Radio *	Ericsson RRU11	B13	19.7	17	7.2	1.40	2.3	51.60	0	0.00	0.00	0.00
	Ericsson RRU12	B5	20.4	18.5	7.5	1.64	2.6	58.00	0	0.00	0.00	0.00
	Ericsson RRU12	B65A	23.07	12.05	7	1.13	1.9	52.90	0	0.00	0.00	0.00
	Ericsson	B2	23.07	12.05	7	1.13	1.9	52.90	0	0.00	0.00	0.00
	Ericsson	4449	17.91	13.19	9.45	1.29	1.6	70.55	1	1.29	70.55	Future
	Ericsson	8843	17.91	13.19	10.9	1.49	1.6	71.87	1	1.49	71.87	Future
	Ericsson	4408 (CRS)	8.39	7.87	4.92	0.19	0.5	11.02	1	0.19	11.02	Future
	Ericsson	2208 (CRS)	7.87	7.87	3.94	0.14	0.4	8.82	0	0.00	0.00	0.00
Power Unit *	Ericsson	2205 (LA)	7.87	7.87	3.94	0.14	0.4	8.82	0	0.00	0.00	0.00
	Ericsson	6502	12.99	11.42	3.90	0.33	BEHIND RRU	22.05	2	0.67	44.09	Future
	Ericsson	PSUAC 02	7.06	13	2.7	0.14	BEHIND RRU	11.50	0	0.00	0.00	0.00
	Ericsson	PSUAC 08	7.07	10.8	2.7	0.12	BEHIND RRU	11.50	0	0.00	0.00	0.00
Disconnect	Square D	QD8161000B	12.6	8.9	4.3	0.28	0.8	9.77	1	0.28	9.77	New
	NRG Term Box	NHG1212B9002	12.13	12.13	8.13	0.69	1.0	10	0	0.00	0.00	0.00
	Hoffman	A16106CH (***)	16	10	6	0.56	1.1	12	1	0.56	12.00	New
	Charles CFT	M12LUFRBLT	12	9	6.1	0.38	0.8	10	0	0.00	0.00	0.00
	CWDM Rittal	AE 1032.500	11.81	7.87	4.72	0.25	0.6	7.93	0	0.00	0.00	0.00
Fiber Terminal (On pole)	Commscope	6389	13.78	12.01	3.98	0.38	1.1	17.64	0	0.00	0.00	0.00
Splitter *	Commscope	MHT-05H-2001-A0500F	11.73	5.13	3.5	0.12	0.4	2.18	0	0.00	0.00	0.00
	Commscope	S-3CPUSE-H-DIG6	6.5	2.87	1.93	0.02	0.1	2.38	0	0.00	0.00	0.00
	Commscope	S-2CPUSE-H-DIG6	6.14	2.87	0.98	0.03	0.1	0.84	0	0.00	0.00	0.00
	Commscope	S-2-CPUSE-H-1316	6.02	2.6	0.98	0.01	0.1	0.64	0	0.00	0.00	0.00
Diplexer *	Commscope	CBC1212X-DS-2X	7.6	7.6	5.5	0.18	0.4	14.2	0	0.00	0.00	0.00
	Commscope	CRIC1937Q3-43	4.5	8.3	3.3	0.07	0.3	8	0	0.00	0.00	0.00
Triplexer *	Commscope	CRG16193-3F-DS-43	6.9	7.8	4.5	0.14	0.4	14.3	0	0.00	0.00	0.00
Quadruplexer *	Commscope	CRG1781921WT-DS	7	11.14	4.72	0.21	0.5	20.1	0	0.00	0.00	0.00
	Commscope	CRG178-DF-2X	7.9	5.9	5.7	0.15	0.3	13.9	0	0.00	0.00	0.00
	Commscope	CM-88D	4.99	8.29	1.39	0.03	0.3	4.9	0	0.00	0.00	0.00
	Microdab X4	CM-79	3.2	6.85	1.48	0.02	0.2	2.4	0	0.00	0.00	0.00
	Microdab X2	DIRC-A-P45F	7.32	6.14	6.38	0.17	0.3	15.2	1	0.17	15.20	Future

{*) Total Volume (CU FT): 5.14

8.49 357.50

PROJECT # 20171626078
LOCATION # 456201
BURLINGTON AND ARTHUR SC
1 ARTHUR AVE
CLARENDON HILLS, IL 60514

SHEET TITLE: **EQUIPMENT SPECIFICATIONS**
SHEET NUMBER: **A-4E**

1 PROPOSED EQUIPMENT SPECIFICATIONS

1

NOTE:
** GC TO REFER TO IEDS SHEET FOR FINAL EQUIPMENT DESIGN AND SPECIFICATIONS. THIS DRAWING IS FOR INFORMATION ONLY AND IS NOT A CONTRACT DOCUMENT. CONCURRENCE IN THIS DRAWING DOES NOT CONSTITUTE AN AGREEMENT TO PURCHASE. THIS DRAWING IS THE PROPERTY OF CONCORDIA GROUP OF COMPANIES. DO NOT COPY, REPRODUCE, REVERSE ENGINEER OR REPLICATE ANY PARTS OF THESE DOCUMENTS IN ANY MANNER. WITHOUT OBTAINING WRITTEN CONSENT FROM THE CONCORDIA GROUP.



CHICAGO
SMSA

limited partnership
dba a VERIZON WIRELESS



DRAWN BY: MK
CHECKED BY: GMS
APPROVED BY: GMS

DRAWN BY: RH
CHECKED BY: GMS
APPROVED BY: GMS



SIDE-BY-SIDE RRU MOUNT CONNECTION

1

SCALE: 2" = 1"

SHEET TITLE
EQUIPMENT
MOUNTING DETAILS

SHEET NUMBER:
A-5

PROJECT #: 20171626078
LOCATION #: 456201
1 ARTHUR SC
CLARENDON HILLS, IL 60514

**CHICAGO
SMSA**
limited partnership
d/b/a VERIZON WIRELESS

CONCORDIA LTD
A PROFESSIONAL DESIGN FIRM
LICENSE # 3323-011-D.A.
CONCORDIA WIRELESS, INC.
361 RANDY ROAD
UNIT 101
CAROL STREAM, IL 60188
MAIN: (847) 881-0801

DRAWN BY: JMK
CHECKED BY: GMS
APPROVED BY: GMS

USE ONLY HIGHLINE HL44
OR SHAKESPEARE PTW1
FOR POLE TOP EXTENSIONS

MOUNT SPECIFICATIONS:
PERFECT VISION NODE#:
PV-PTM-S-13-4-238xx (")
MATERIAL: GALVANIZED STEEL
WEIGHT: 235 LBS
(ANTENNA PIPE HARDWARE INCLUDED)


NOTE:

* GC TO REFER TO BIDS SHEET FOR FINAL
EQUIPMENT CONFIGURATION AND ANTENNA
POLE TOP MOUNT. MACRO, ERICSSON, AND
ERICSSON RAN 448 AND 446 RADIO UNITS
CX101024-250 UNITS SHOWN

** VERTICAL SEPARATION BETWEEN CANISTER
ANTENNA AND RADIO (WIRELESS) ANTENNA
CONFIGURATION. SEPARATION BETWEEN
ERICSSON STREET MACRO 670 AND JMA
WIRELESS CX101024-250 UNITS SHOWN

*** GC TO SPECIFY PIPE LENGTH AT THE
TIME OF ORDER

**** GC TO DEMONSTRATE CONDITIONS & CUT
STANDARD 20' PIPE PROVIDED BY
MANUFACTURER TO REQUIRED LENGTH &
ORDER POLE EXTENSION ACCORDINGLY TO
MEET SITE CLEARANCES (MAY VARY PER SITE)




PROJECT #: 20171626078
LOCATION #: 165201
BURLINGTON AND ARTHUR SC
1 ARTHUR AVE
CLARENDON HILLS, IL 60514

SHEET TITLE
ANTENNA MOUNT & POLE
EXTENSION DETAILS
SHEET NUMBER:
A-5A

NOTE:
BOL HOLE LAYOUT TO BE
DRILLED IN THE FIELD BY GC

<p>CHICAGO SMSA limited partnership d/b/a VERIZON WIRELESS</p>		<p>CONCORDIA, LTD. DESIGN FIRM LICENSE # 4322511-D-B-A ONCORDIA WIRELESS, INC. 361 RANDY ROAD UNIT 101 CARO STREAM, 60163 ILLINOIS (630) 581-0501</p>	
<p>NOTE: SHOWING SEPARATE SHEET AND IF REASONABLE, ANTENA PIPE POSITION TO BE ADJUSTED IN THE FIELD BY GO TO TEST FOLLOW EQUIPMENT MANUFACTURER'S SPACING RECOMMENDATIONS</p>		<p>*** GO TO REFER TO IFPS SHEET FOR FINAL EQUIPMENT ENSON STREET MICRO SITE AND ERICSSON RADIO 4400 UNITS SHOWN</p>	
<p>WHEN USING POLE TOP EXTENSION: • USE ONLY HIGHLINE HL44 OR SHAKESPEARE PTX/PTR MATERIAL: GALVANIZED STEEL WEIGHT: 2.55 LBS (ANTENNA PIPE HARDWARE INCLUDED)</p>		<p>*** GO TO SPECIFY PIPE LENGTH AT TIME OF ORDER STANDARD 3/8" PIPE PROVIDED BY MANUFACTURER TO REQUIRED LENGTH & ORDER POLE EXTENSION ACCURATELY TO MEET SITE CLEARANCES (VARIES PER SITE)</p>	
<p>PROJECT # 20171626078 LOCATION # 156201 1 ARTHUR SC CLARENDON HILLS, IL 60514</p>		<p>1 SCALE: 1:87 (1'-1 1/2" = 1'11" SHEET SIZE)</p>	
<p>DRAWN BY: MK CHECKED BY: RH</p>		<p>CHECKED BY: GMS APPROVED BY: GMS</p>	
<p>1 RADIOS W/INTEGRATED ANTENNAS & CBRSS RADIO TYPICAL MOUNTING DETAIL (PLAN VIEW)</p>		<p>SHEET TITLE EQUIPMENT MOUNTING DETAILS</p>	
<p>SHEET NUMBER A-5B</p>		<p>SHEET NUMBER A-5B</p>	




CHICAGO SMSA

limited partnership
d/b/a VERIZON WIRELESS


CONCORDIA LTD. DESIGN FIRM
LICENSE # 8320101 D.A.

CONCORDIA WIRELESS, INC.
361 RANDY ROAD
UNIT 101
CAROL STREAM, IL 60163
MATT: (847) 881-0001

DRAWN BY: MK
CHECKED BY: GMS
APPROVED BY: GMS



SYMBOLS LEGEND:



GROUNDING ELECTRODE SYSTEM NOTES:

1. ALL GROUNDING CONNECTIONS SHALL BE MADE BY THE EXOTHERMIC PROCESS CONNECTIONS SHALL INCLUDE ALL CASE TO CABINET SURFACES, ALL METAL GROUNDED CONDUCTION LEADS AS INDICATED BY PM, ALL MATERIAL USED WOULD WELDING METAL, TOOLS, ETC TO SHIELD BE EXOTHERMIC PROCESS AND INSTALLED PER MANUFACTURERS RECOMMENDATION AND PROCEDURES
2. ALL EXOTHERMIC CONNECTIONS ON GALVANIZED SURFACES SHALL BE CLEARED THOROUGHLY AND COLORED TO MATCH SURFACE, WITH (2) TWO CRIMP CAP TERMINAL (PM) 8841 (CR EQUAL) AND PAINT (BROWN OR EQUAL) OR SHREWD WILMINGTON SILVER (PM) 8851 (CR EQUAL)
3. ALL ELECTRICAL MECHANICAL GROUNDING CONNECTIONS SHALL HAVE ANTI-OXIDANT COMPOUND APPLIED TO CONNECTIONS
4. UTILITY COMPANY COORDINATION SECTION OF CONTRACTOR SHALL CONFIRM THAT ALL WORK TO BE PERFORMED IS IN ACCORDANCE WITH THE UTILITY COMPANIES REQUIREMENTS. THE CONTRACTOR SHALL CHECK WITH THE UTILITY COMPANIES SUPPLYING SERVICE TO THIS PROJECT AND SHALL DETERMINE FROM THEM ALL EQUIPMENT AND CHARGE WHICH THEY WILL REQUIRE AND SHALL INCLUDE THE COST IN THE BID
5. GROUND TEST, GROUND RESISTANCE SHALL BE PERFORMED AS REQUIRED BY LESSEE. STANDARD PROCEDURES GROUND GRID RESISTANCE SHALL NOT EXCEED 10 OHMS.
6. CONTRACTOR SHALL SUBMIT THE GROUND RESISTANCE TEST REPORT AS FOLLOWS

1. ONE (1) COPY TO OWNER REPRESENTATIVE
2. ONE (1) COPY TO ENGINEER
3. ONE (1) COPY TO KEEP INSIDE EQUIPMENT ENCLOSURE


4. GROUND ROOD WILL BE 12' X 8' FOOT COPPER CLAD NOT LESS THAN 8 FOOT OR MORE THAN 15 FOOT APART, ALL CONNECTIONS TO THE GROUND ROD AND GROUND RING AND GROUND RING TO GROUND ROD SHALL BE #2 SOLID TINNED COPPER UNLESS OTHERWISE SPECIFIED. ALL GROUND LEADS DENOTED BY (6) SIX SHALL BE INSTALLED IN 12' SCHEDULE 40 PVC ABOVE GROOVE.
5. GROUND TEST, GROUND RESISTANCE SHALL BE PERFORMED AS REQUIRED BY LESSEE.
6. CONTRACTOR SHALL SUBMIT THE GROUND RESISTANCE TEST REPORT AS FOLLOWS

PROJECT #: 20171626078
LOCATION #: 456201
BURLINGTON AND ARTHUR SC
1ARTHUR AVE
CLARENDON HILLS, IL 60514

SHEET TITLE: GROUNDING DETAILS
SHEET NUMBER: G-1

2 TYPICAL EQUIPMENT GROUNDING SCHEMATIC

SAMPLE GROUNDING INSTALLATION PHOTOS



2

SCALE: 1/4"

© Concordia 2001-2020. Copyright Notice: These Documents/Drawings Are Produced by and Are The Property of Concordia Group Of Companies. Do Not Copy, Reproduce, Reverse-Engineer Or Replicate Any Parts of These Documents In Any Manner Without Obtaining Written Consent From The Concordia Group.



Concordia Wireless, Inc.

ConcordiaWireless.Com

Passing @ 98.3%

Structural Calculations **MODIFICATION**

**Analysis of Existing Wooden Utility Pole for the additional
loads due to the attachment of new Lessee equipment**

Project #
20171626078

Location #
456201

Site Name:
BURLINGTON & ARTHUR SC

Site Address
1 ARTHUR AVE
CLARENDON HILLS, IL 60514

Prepared For:

**CHICAGO SMSA
d/b/a VERIZON WIRELESS**

Prepared By:

CONCORDIA WIRELESS

June 23, 2020

I certify that these calculations were prepared
by me or under my supervision and to
the best of my knowledge and belief
comply with the requirements of
the local building code

MD. EXP. 11-30-2020

Nabi R. Fakroddin, P.E., S.E.
Licensed Structural Engineer
Expires: 11-30-2020

PURPOSE

The purpose of this analysis was to verify the structural adequacy of an existing utility pole to resist new and existing equipment loads.

DESCRIPTION

Based on measurements taken in the field, the existing pole is 35-ft long, class 4 of assumed Southern Yellow Pine. The analysis was performed assuming an embedment of 5'-5"; thus, the pole extends approximately 29'-7" above grade. We assumed the pole embedment is sufficient to support all loads.

ANALYSIS PROCEDURE AND RESULTS

The pole was subjected to the ANSI C2-2017 (NESC 2017) Code standards. The following loading cases were considered:

1. Rule 250B - Grade C: Forces due to a wind speed of 40 mph in conjunction with 0.50-inch ice build-up around all elements (i.e. Heavy Loading District).
2. Rule 250C - Grade C: Forces due to a wind speed of 90 mph (i.e. Extreme Wind).

Pole Rating: 98.3%

CONCLUSION


Based on the performed calculations, the utility pole is structurally acceptable to resist the loads imposed by the existing and the proposed equipment.

NEW CONFIG												
Cat	Item	Model	Dimensions (inches)			Volume	Area	Weight	Number	Total Volume	Total Weight	Note
			H	W	D							
Antennas	Amphenol	QXW-632x634xBF-EDIN	23.2	12	7.1	1.14	1.9	11	0	0.00	0.00	
	Amphenol	CUUX063X06Fxyz0	24.3	12.1	7	1.19	2.0	13	0	0.00	0.00	
	Amphenol	CWT070X06F00-1	24	14.6 (Dia)		2.33	n/a	28.70	0	0.00	0.00	
	Amphenol	CUT070X06F00-1	24	14.6 (Dia)		2.33	n/a	22.00	0	0.00	0.00	
	Kathrein	840-10794	24.6	16 (Dia)		2.86	n/a	39.90	0	0.00	0.00	
	Kathrein	840-10510	24	16 (Dia)		2.79	n/a	45.00	0	0.00	0.00	
	Kathrein	840-10515	24	16 (Dia)		2.79	n/a	50.00	0	0.00	0.00	
	JMA	CX180MI236-1Cxy	24	14.6 (Dia)		2.33	n/a	30.00	1	2.33	30.00	Future
	JMA	CX040MI236-1C	27.5	14 (Dia)		2.45	n/a	38.60	0	0.00	0.00	
	JMA	XGU-165	12	12.6	5.6	0.49	1.1	10.80	0	0.00	0.00	
Radio / Antenna *	Ericsson	AIR 5331 (**)	23.62	11.93	6.26	1.02	2.0	30.86	0	0.00	0.00	
	Ericsson	AIR 5121 (**)	23.94	11.81	5.67	0.93	2.0	30.86	0	0.00	0.00	
	Ericsson	STREETMACRO 6701 (**)	21.20	8.10	5.10	0.51	1.2	31.00	3	1.52	93.00	New
	Ericsson	DUAL RADIO SUPPORT (6503)	17.13	7.87	5.28	0.41	0.9	21.60	0	0.00	0.00	
Radio *	Ericsson RRUS11	B13	19.7	17	7.2	1.40	2.3	51.00	0	0.00	0.00	
	Ericsson RRUS12	B5	20.4	18.5	7.5	1.64	2.6	58.00	0	0.00	0.00	
	Ericsson RRUS 32	B66A	23.07	12.05	7	1.13	1.9	52.90	0	0.00	0.00	
	Ericsson RRUS 32	B2	23.07	12.05	7	1.13	1.9	52.90	0	0.00	0.00	
	Ericsson	4449	17.91	13.19	9.45	1.29	1.6	70.55	1	1.29	70.55	Future
	Ericsson	8843	17.91	13.19	10.9	1.49	1.6	71.87	1	1.49	71.87	Future
	Ericsson	4408 (CBRS)	8.39	7.87	4.92	0.19	0.5	11.02	1	0.19	11.02	Future
	Ericsson	2208 (CBRS)	7.87	7.87	3.94	0.14	0.4	8.82	0	0.00	0.00	
	Ericsson	2205 (LAA)	7.87	7.87	3.94	0.14	0.4	8.82	0	0.00	0.00	
	Power Unit *	6302	12.99	11.42	3.90	0.33	BEHIND RRU	22.05	2	0.67	44.09	Future
Fiber box	Ericsson	PSU AC 02	7.06	13	2.7	0.14	BEHIND RRU	11.50	0	0.00	0.00	
	Ericsson	PSU AC 08	7.07	10.8	2.7	0.12	BEHIND RRU	11.50	0	0.00	0.00	
	Disconnect	Square D	Q0816L100RB	12.6	8.9	4.3	0.28	0.8	9.77	1	0.28	9.77
Fiber Terminal (On pole)	NRG Term Box	NHC12128002	12.13	12.13	8.13	0.69	1.0	10	0	0.00	0.00	
	Hoffman	A16106CH (**)	16	10	6	0.56	1.1	12	1	0.56	12.00	New
	Charles CFIT	M12LUFBRLT	12	9	6.1	0.38	0.8	10	0	0.00	0.00	
	CWDM Rittal	AE 1032.500	11.81	7.87	4.72	0.25	0.6	7.93	0	0.00	0.00	
	Ericsson	6389	13.78	12.01	3.98	0.38	1.1	17.64	0	0.00	0.00	
Splitter *	Commscope	MHT-06H200U-A0500F	11.73	5.13	3.5	0.12	0.4	2.18	0	0.00	0.00	
	Commscope	S-3CPUSE-H-Di6	6.5	2.87	1.93	0.02	0.1	2.38	0	0.00	0.00	
	Commscope	S-2CPUSE-H-Di6	6.14	2.87	0.98	0.01	0.1	0.84	0	0.00	0.00	
	Commscope	S-2-CPUSE-H-43-i6	6.02	2.6	0.98	0.01	0.1	0.64	0	0.00	0.00	
Diplexer *	Commscope	CBC1921X-DS-2X	7.6	7.6	5.5	0.18	0.4	14.2	0	0.00	0.00	
	Commscope	CBC1923Q-43	4.5	8.3	3.3	0.07	0.3	8	0	0.00	0.00	
	Commscope	CBC61923T-DS-43	6.9	7.8	4.5	0.14	0.4	14.3	0	0.00	0.00	
Triplexer *	Commscope	CBC781921WT-DS	7	11.14	4.72	0.21	0.5	20.1	0	0.00	0.00	
	Commscope	CBC1923Q-43	4.5	8.3	3.3	0.07	0.3	8	0	0.00	0.00	
Quadplexer *	Commscope	CBC781921WT-DS	7	11.14	4.72	0.21	0.5	20.1	0	0.00	0.00	
	Commscope	CBC78-DF-2X	7.9	5.9	5.7	0.15	0.3	13.9	0	0.00	0.00	
Coupler *	Commscope	CBC4X4	4.99	8.29	1.39	0.03	0.3	4.9	0	0.00	0.00	
	Commscope	CM-3X2	3.2	6.85	1.48	0.02	0.2	2.4	0	0.00	0.00	
Combiner *	Microlab 4X4	CM-88D	4.99	8.29	1.39	0.03	0.3	4.9	0	0.00	0.00	
	Microlab 3X2	CM-79	3.2	6.85	1.48	0.02	0.2	2.4	0	0.00	0.00	
JMA	DBC-A-P-4SF	7.32	6.14	6.38	0.17	0.3	15.2	1	0.17	15.20	Future	
									8.49	357.50		

(*) Total Volume (CU FT) :

5.14

Pole Num:	456201	Pole Length / Class:	35 / 4	Code:	NESC	Structure Type:	Guyed Tangent
Aux Data 1	Unset	Species:	SOUTHERN PINE	NESC Rule:	Rule 250B	Status	Guy Wires Adequate
Aux Data 2	Unset	Setting Depth (ft):	5.42	Construction Grade:	C	Pole Strength Factor:	0.85
Aux Data 3	Unset	G/L Circumference (in):	31.86	Loading District:	Heavy	Transverse Wind LF:	1.75
Aux Data 4	Unset	G/L Fiber Stress (psi):	8,000	Ice Thickness (in):	0.50	Wire Tension LF:	1.30
Aux Data 5	Unset	Allowable Stress (psi):	6,800	Wind Speed (mph):	39.53	Vertical LF:	1.90
Aux Data 6	Unset	Fiber Stress Ht. Reduc:	No	Wind Pressure (psf):	4.00		
Latitude:		Longitude:	0	Elevation:	0		0M



Pole Capacity Utilization (%)		Height (ft)	Wind Angle (deg)
Maximum	72.3	0.0	180.0
Groundline	72.3	0.0	180.0
Vertical	4.2	21.92	270.0

Pole Moments (ft-lb)		Load Angle (deg)	Wind Angle (deg)
Max Cap Util	41,104	183.9	180.0
Groundline	41,104	183.9	180.0
GL Allowable	58,025		

Guy System Component Summary				Load From Worst Wind Angle on Pole		Individual Maximum Load With Overload Applied	
Description	Lead Length (ft)	Lead Angle (deg)	Height (ft)	Nominal Capacity (%)	Wind Angle (deg)	Max* Load Capacity (%)	Wind Angle (deg)
Expanding - 12" - Soil Class 3	13.0	90.0		4.2	180.0	7.2	270.0
EHS 1/2 (Down)			18.9	6.9	180.0	11.8	270.0
System Capacity Summary:				Adequate		Adequate	

Groundline Load Summary - Reporting Angle Mode: Load - Reporting Angle: 183.9°										
	Shear Load* (lbs)	Applied Load (%)	Bending Moment (ft-lb)	Applied Moment (%)	Pole Capacity (%)	Bending Stress (+/- psi)	Vertical Load (lbs)	Vertical Stress (psi)	Total Stress (psi)	Pole Capacity (%)
Powers	640	46.3	24,133	58.7	41.6	2,743	1,645	20	2,763	40.6
Comms	423	30.6	8,868	21.6	15.3	1,008	1,183	15	1,023	15.0
GuyBraces	-51	-3.7	-998	-2.4	-1.7	-114	2,110	26	-87	-1.3
GenericEquipments	188	13.6	4,342	10.6	7.5	494	1,251	15	509	7.5
Pole	145	10.5	2,304	5.6	4.0	262	1,320	16	278	4.1
Crossarms	2	0.1	367	0.9	0.6	42	76	1	43	0.6
Streetlights	32	2.3	1,973	4.8	3.4	224	162	2	226	3.3
Insulators	4	0.3	115	0.3	0.2	13	82	1	14	0.2
Pole Load	1,381	100.0	41,104	100.0	70.8	4,672	7,828	97	4,769	70.1
Pole Reserve Capacity			16,921		29.2	2,128			2,031	29.9

Load Summary by Owner - Reporting Angle Mode: Load - Reporting Angle: 183.9°										
	Shear Load* (lbs)	Applied Load (%)	Bending Moment (ft-lb)	Applied Moment (%)	Pole Capacity (%)	Bending Stress (+/- psi)	Vertical Load (lbs)	Vertical Stress (psi)	Total Stress (psi)	Pole Capacity (%)
<Undefined>	1,197	86.6	37,865	92.1	65.3	4,304	6,423	80	4,383	64.5
Verizon	40	2.9	935	2.3	1.6	106	86	1	107	1.6
Pole	145	10.5	2,304	5.6	4.0	262	1,320	16	278	4.1
Totals:	1,381	100.0	41,104	100.0	70.8	4,672	7,828	97	4,769	70.1

Detailed Load Components:

Power	Owner	Height (ft)	Horiz. Offset (in)	Cable Diameter (in)	Sag at Max Temp (ft)	Cable Weight (lbs/ft)	Lead/Span Length (ft)	Span Angle (deg)	Wire Length (ft)	Tension (lbs)	Tension Moment* (ft-lb)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Primary	AAC 795.0 KCM 37 STRAND ARBUTUS	29.73	88.18	1.0260	1.69	0.745	162.0	90.0	162.0	4,170	-10,917	1,899	2,843	-6,174
Primary	AAC 795.0 KCM 37 STRAND ARBUTUS	29.73	88.18	1.0260	0.78	0.745	94.0	270.0	94.0	4,170	10,917	1,102	1,650	13,669
Primary	AAC 795.0 KCM 37 STRAND ARBUTUS	29.73	20.78	1.0260	1.69	0.745	162.0	90.0	162.0	4,170	-10,917	425	2,843	-7,648
Primary	AAC 795.0 KCM 37 STRAND ARBUTUS	29.73	20.78	1.0260	0.78	0.745	94.0	270.0	94.0	4,170	10,917	247	1,650	12,814
Primary	AAC 795.0 KCM 37 STRAND ARBUTUS	29.73	50.32	1.0260	1.69	0.745	162.0	90.0	162.0	4,170	-10,917	1,076	2,843	-6,998
Primary	AAC 795.0 KCM 37 STRAND ARBUTUS	29.73	50.32	1.0260	0.78	0.745	94.0	270.0	94.0	4,170	10,917	624	1,650	13,191

Neutral	AAC 250 KCM 19 STRAND VALERIAN	24.92	6.11	0.5740	0.75	0.234	94.0	270.0	94.0	1,400	3,068	-41	1,073	4,100		
Secondary	TRIPLEX 6 AWG	24.92	6.11	0.5800	2.01	0.113	162.0	90.0	162.0	500	-1,096	-61	1,856	699		
Secondary	TRIPLEX 1/0	24.25	6.15	1.0300	2.17	0.399	162.0	90.0	162.0	1,200	-2,559	-7	2,321	-245		
												Totals:	-587	5,264	18,730	23,407

Comm	Owner	Height (ft)	Horiz. Offset (in)	Cable Diameter (in)	Sag at Max Temp (ft)	Cable Weight (lbs/ft)	Lead/Span Length (ft)	Span Angle (deg)	Wire Length (ft)	Tension (lbs)	Tension Moment* (ft-lb)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)		
Overlashed Bundle	6M	19.67	6.41	0.2420	6.35	0.104	162.0	90.0	162.0	1,200	-2,076	36	1,316	-723		
CATV	CATV .75	19.64	5.87	1.0700		0.900	162.0	90.0	162.0			93	388	481		
CATV	CATV .50	19.65	6.68	0.5700		0.600	162.0	90.0	162.0			80	388	469		
CATV	CATV .50	19.60	6.55	0.5700		0.600	162.0	90.0	162.0			79	388	466		
Overlashed Bundle	6M	19.67	6.41	0.2420	2.25	0.104	94.0	270.0	94.0	1,200	2,076	21	764	2,860		
CATV	CATV .75	19.64	6.95	1.0700		0.900	94.0	270.0	94.0			64	225	289		
CATV	CATV .50	19.65	6.14	0.5700		0.600	94.0	270.0	94.0			43	225	268		
CATV	CATV .50	19.60	6.27	0.5700		0.600	94.0	270.0	94.0			44	225	269		
Overlashed Bundle	1/4" EHS	18.92	6.46	0.2500	3.14	0.121	90.0	90.0	90.0	250	-416	-2	695	277		
CATV	CATV .50	18.89	6.46	0.5700		0.600	90.0	90.0	90.0			-3	199	196		
Overlashed Bundle	6M	18.92	6.46	0.2420	0.86	0.104	94.0	270.0	94.0	1,500	2,496	2	761	3,258		
CATV	CATV .50	18.90	6.46	0.5700		0.600	94.0	270.0	94.0			5	243	248		
Telco	P3-750JCA	18.89	6.47	0.8200		0.197	94.0	270.0	94.0			0	243	243		
												Totals:	2,080	462	6,059	8,601

GenericEquipment	Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Cylinder	OMNI ANTENNA	36.58	1.07	0.0	0.0	10.00	24.60	--	16.00	--	2	698	700
Box	Bracket 01B	34.75	0.04	180.0	0.0	34.00	18.00	2.00	--	3.00	0	146	146
Box	PANEL ANTENNA	34.00	12.21	0.0	0.0	30.86	23.62	6.26	--	11.93	-60	743	684
Box	Bracket 02A	34.00	6.08	0.0	0.0	34.00	12.00	2.00	--	3.00	-33	16	-17
Box	PANEL ANTENNA	34.00	12.21	180.0	0.0	30.86	23.62	6.26	--	11.93	60	743	803
Box	Bracket 02A	34.00	6.08	180.0	0.0	34.00	12.00	2.00	--	3.00	33	16	49
Box	PANEL ANTENNA	34.00	12.21	270.0	0.0	30.86	23.62	6.26	--	11.93	4	390	394
Box	Bracket 02A	34.00	6.08	270.0	0.0	34.00	12.00	2.00	--	3.00	2	63	66
Cylinder	HL-44	32.33	0.32	0.0	0.0	25.00	66.00	--	7.00	--	1	724	726
Box	TRIPLEX	15.00	14.38	20.0	0.0	21.60	7.32	6.38	--	6.14	-47	53	5
Cylinder	Radio Mount 01	14.50	5.72	0.0	90.0	40.00	53.25	--	3.00	--	-36	112	76
Box	RRU UNIT	14.00	22.63	50.0	0.0	92.00	17.08	12.75	--	13.50	-228	243	14
Box	POWER BOX	14.00	18.20	85.0	0.0	22.20	12.99	3.89	--	11.42	-10	56	46
Box	RRU UNIT	14.00	22.63	310.0	0.0	92.00	17.08	12.75	--	13.50	-194	242	48

Box	POWER BOX	14.00	18.20	280.0	0.0	22.20	12.99	3.89	--	11.42	-7	57	50		
Cylinder	Radio Mount 01	14.00	5.75	0.0	90.0	40.00	53.25	--	3.00	--	-36	108	72		
Box	Fiber Box	Verizon	11.13	8.92	90.0	0.0	10.00	16.00	7.00	--	10.00	-1	97	96	
Box	Breaker Box	Verizon	11.00	6.58	0.0	0.0	10.00	12.60	4.30	--	8.90	-10	96	85	
Box	Bracket 02A		34.00	6.08	90.0	0.0	34.00	12.00	2.00	--	3.00	-2	63	61	
Box	CBRS RADIO		34.00	11.54	90.0	0.0	11.02	8.40	4.92	--	7.90	-1	109	108	
												Totals:	-565	4,776	4,212

Crossarm	Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)	
Offset	ALLEY ARM 3-1/2 X 4-1/2 X 6	28.88	5.63	90.0	90.0	40.00	5.50	4.50	96.00	301	55	356	
										Totals:	301	55	356

Streetlight	Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)	
General	Streetlight - 10 ft. Arm	22.38	3.76	180.0	180.0	85.00	24.00	20.00	3.00	120.00	1,197	716	1,914	
											Totals:	1,197	716	1,914

Insulator	Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)		
Pin	Pin Insulator - 5 kV	29.10	88.00	176.3	0.0	6.00	3.50	7.50	0	37	37		
Pin	Pin Insulator - 5 kV	29.10	20.00	164.3	0.0	6.00	3.50	7.50	0	37	37		
Pin	Pin Insulator - 5 kV	29.10	50.00	173.6	0.0	6.00	3.50	7.50	0	37	37		
J-Hook	J-Hook	19.67	0.00	180.0	180.0	5.00	3.00	0.00	0	0	0		
J-Hook	J-Hook	24.92	0.00	0.0	0.0	5.00	3.00	0.00	0	0	0		
J-Hook	J-Hook	24.25	0.00	90.0	90.0	5.00	3.00	0.00	0	0	0		
J-Hook	J-Hook	18.92	0.00	90.0	90.0	5.00	3.00	0.00	0	0	0		
J-Hook	J-Hook	18.92	0.00	270.0	270.0	5.00	3.00	0.00	0	0	0		
										Totals:	0	111	111

Guy Wire and Brace	Owner	Attach Height (ft)	End Height (ft)	Lead/Span Length (ft)	Wire Diameter (in)	Percent Solid (%)	Lead Angle (deg)	Incline Angle (deg)	Wire Weight (lbs/ft)	Rest Length (ft)	Stretch Length (in)
EHS 1/2	Down	18.92	0.00	13.00	0.5	75.00	90.0	55.3	0.517	27.44	0.16


Guy Wire and Brace (Loads and Reactions)	Elastic Modulus (psi)	Rated Tensile Strength (lbs)	Guy Strength Factor	Allowable Tension (lbs)	Initial Tension (lbs)	Loaded Tension* ² (lbs)	Maximum Tension ² (lbs)	Applied Tension ³ (lbs)	Vertical Load (lbs)	Shear Load In Guy Dir (lbs)	Shear Load At Report Angle (lbs)	Moment at GL ³ (ft-lb)		
EHS 1/2	Down	2.30e+7	26,900	0.90	24,210	700	2,865	2,604	1,676	1,378	954	-65	-968	
										Totals:	1,378	954	-65	-968

Anchor/Rod Load Summary		Owner	Rod Length AGL (in)	Lead Length (ft)	Lead Angle (deg)	Strength of Assembly (lbs)	Anchor/Rod Strength Factor	Allowable Load (lbs)	Max Load ² (lbs)	Load at Pole MCU ³ (lbs)	Max Required Capacity ² (%)
Expanding - 12" - Soil Class 3			0.00	13.00	90.0	40,000	1.00	40,000	2,865	1,676	7.2

Pole Buckling

Buckling Constant	Buckling Column Height* (ft)	Buckling Section Height (% Buckling Col. Hgt.)	Buckling Section Diameter (in)	Minimum Buckling Diameter at GL (in)	Diameter at Tip (in)	Diameter at GL (in)	Modulus of Elasticity (psi)	Pole Density (pcf)	Ice Density (pcf)	Pole Tip Height (ft)	Buckling Load Capacity at Height (lbs)	Buckling Load Applied at Height (lbs)	Buckling Load Factor of Safety
0.71	21.93	33.79	9.28	4.58	6.69	10.15	2.13e+6	60.00	57.00	29.58	187,451	1863.88	23.81

Pole Num:	456201	Pole Length / Class:	35 / 4	Code:	NESC	Structure Type:	Guyed Tangent
Aux Data 1	Unset	Species:	SOUTHERN PINE	NESC Rule:	Rule 250C	Status	Guy Wires Adequate
Aux Data 2	Unset	Setting Depth (ft):	5.42	Construction Grade:	C	Pole Strength Factor:	0.75
Aux Data 3	Unset	G/L Circumference (in):	31.86	Loading District:	Special	Transverse Wind LF:	0.87
Aux Data 4	Unset	G/L Fiber Stress (psi):	8,000	Ice Thickness (in):	0.00	Wire Tension LF:	1.00
Aux Data 5	Unset	Allowable Stress (psi):	6,000	Wind Speed (mph):	90.00	Vertical LF:	1.00
Aux Data 6	Unset	Fiber Stress Ht. Reduc:	No	Wind Pressure (psf):	20.74	Max 250C Wind (mph)	92.91
Latitude:		Longitude:	0	Elevation:	0		0M



Pole Capacity Utilization (%)		Height (ft)	Wind Angle (deg)
Maximum	98.3	0.0	180.0
Groundline	98.3	0.0	180.0
Vertical	1.8	20.92	270.0

Pole Moments (ft-lb)		Load Angle (deg)	Wind Angle (deg)
Max Cap Util	49,975	182.2	180.0
Groundline	49,975	182.2	180.0
GL Allowable	51,199		

Guy System Component Summary				Load From Worst Wind Angle on Pole		Individual Maximum Load With Overload Applied	
Description	Lead Length (ft)	Lead Angle (deg)	Height (ft)	Nominal Capacity (%)	Wind Angle (deg)	Max* Load Capacity (%)	Wind Angle (deg)
Expanding - 12" - Soil Class 3	13.0	90.0		3.4	180.0	8.9	270.0
EHS 1/2 (Down)			18.9	5.6	180.0	14.7	270.0
System Capacity Summary:				Adequate		Adequate	

Groundline Load Summary - Reporting Angle Mode: Load - Reporting Angle: 182.2°

	Shear Load* (lbs)	Applied Load (%)	Bending Moment (ft-lb)	Applied Moment (%)	Pole Capacity (%)	Bending Stress (+/- psi)	Vertical Load (lbs)	Vertical Stress (psi)	Total Stress (psi)	Pole Capacity (%)
Powers	685	35.1	21,811	43.6	42.6	2,427	339	4	2,431	40.5
Comms	432	22.1	8,952	17.9	17.5	996	357	4	1,000	16.7
GuyBraces	-19	-1.0	-382	-0.8	-0.8	-43	1,130	14	-28	-0.5
GenericEquipments	439	22.5	11,820	23.7	23.1	1,315	659	8	1,323	22.1
Pole	326	16.7	4,730	9.5	9.2	526	695	9	535	8.9
Crossarms	5	0.2	310	0.6	0.6	35	40	0	35	0.6
Streetlights	76	3.9	2,447	4.9	4.8	272	85	1	273	4.6
Insulators	9	0.5	287	0.6	0.6	32	43	1	32	0.5
Pole Load	1,952	100.0	49,975	100.0	97.6	5,560	3,347	41	5,601	93.4
Pole Reserve Capacity			1,224		2.4	440			399	6.6

Load Summary by Owner - Reporting Angle Mode: Load - Reporting Angle: 182.2°

	Shear Load* (lbs)	Applied Load (%)	Bending Moment (ft-lb)	Applied Moment (%)	Pole Capacity (%)	Bending Stress (+/- psi)	Vertical Load (lbs)	Vertical Stress (psi)	Total Stress (psi)	Pole Capacity (%)
<Undefined>	1,534	78.6	42,930	85.9	83.9	4,776	2,607	32	4,808	80.1
Verizon	92	4.7	2,315	4.6	4.5	258	45	1	258	4.3
Pole	326	16.7	4,730	9.5	9.2	526	695	9	535	8.9
Totals:	1,952	100.0	49,975	100.0	97.6	5,560	3,347	41	5,601	93.4

Detailed Load Components:

Power	Owner	Height (ft)	Horiz. Offset (in)	Cable Diameter (in)	Sag at Max Temp (ft)	Cable Weight (lbs/ft)	Lead/Span Length (ft)	Span Angle (deg)	Wire Length (ft)	Tension (lbs)	Tension Moment* (ft-lb)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Primary	AAC 795.0 KCM 37 STRAND ARBUTUS	29.73	88.18	1.0260	2.27	0.745	162.0	90.0	162.0	4,170	-4,690	441	3,109	-1,139
Primary	AAC 795.0 KCM 37 STRAND ARBUTUS	29.73	88.18	1.0260	1.07	0.745	94.0	270.0	94.0	4,170	4,690	256	1,872	6,818
Primary	AAC 795.0 KCM 37 STRAND ARBUTUS	29.73	20.78	1.0260	2.27	0.745	162.0	90.0	162.0	4,170	-4,690	99	3,109	-1,481
Primary	AAC 795.0 KCM 37 STRAND ARBUTUS	29.73	20.78	1.0260	1.07	0.745	94.0	270.0	94.0	4,170	4,690	58	1,872	6,620
Primary	AAC 795.0 KCM 37 STRAND ARBUTUS	29.73	50.32	1.0260	2.27	0.745	162.0	90.0	162.0	4,170	-4,690	250	3,109	-1,330
Primary	AAC 795.0 KCM 37 STRAND ARBUTUS	29.73	50.32	1.0260	1.07	0.745	94.0	270.0	94.0	4,170	4,690	145	1,872	6,707

Neutral	AAC 250 KCM 19 STRAND VALERIAN	24.92	6.11	0.5740	1.24	0.234	94.0	270.0	94.0	1,400	1,318	-6	858	2,170
Secondary	TRIPLEX 6 AWG	24.92	6.11	0.5800	2.47	0.113	162.0	90.0	162.0	500	-471	-5	1,439	964
Secondary	TRIPLEX 1/0	24.25	6.15	1.0300	2.41	0.399	162.0	90.0	162.0	1,200	-1,099	-1	2,477	1,377
													Totals:	-252 1,239 19,719 20,706

Comm	Owner	Height (ft)	Horiz. Offset (in)	Cable Diameter (in)	Sag at Max Temp (ft)	Cable Weight (lbs/ft)	Lead/Span Length (ft)	Span Angle (deg)	Wire Length (ft)	Tension (lbs)	Tension Moment* (ft-lb)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Overlashed Bundle	6M	19.67	6.41	0.2420	7.01	0.104	162.0	90.0	162.0	1,200	-892	4	793	-94
CATV	CATV .75	19.64	5.87	1.0700		0.900	162.0	90.0	162.0			36	792	828
CATV	CATV .50	19.65	6.68	0.5700		0.600	162.0	90.0	162.0			27	792	819
CATV	CATV .50	19.60	6.55	0.5700		0.600	162.0	90.0	162.0			27	790	817
Overlashed Bundle	6M	19.67	6.41	0.2420	2.69	0.104	94.0	270.0	94.0	1,200	892	3	478	1,373
CATV	CATV .75	19.64	6.95	1.0700		0.900	94.0	270.0	94.0			24	478	502
CATV	CATV .50	19.65	6.14	0.5700		0.600	94.0	270.0	94.0			14	478	492
CATV	CATV .50	19.60	6.27	0.5700		0.600	94.0	270.0	94.0			15	477	491
Overlashed Bundle	1/4" EHS	18.92	6.46	0.2500	3.31	0.121	90.0	90.0	90.0	250	-179	0	421	242
CATV	CATV .50	18.89	6.46	0.5700		0.600	90.0	90.0	90.0			-1	420	420
Overlashed Bundle	6M	18.92	6.46	0.2420	1.70	0.104	94.0	270.0	94.0	1,500	1,072	0	512	1,584
CATV	CATV .50	18.90	6.46	0.5700		0.600	94.0	270.0	94.0			1	512	513
Telco	P3-750JCA	18.89	6.47	0.8200		0.197	94.0	270.0	94.0			0	511	511
												Totals:	893 151 7,455 8,499	

GenericEquipment	Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)
Cylinder	OMNI ANTENNA	36.58	1.07	0.0	0.0	10.00	24.60	--	16.00	--	1	1,756	1,757
Box	Bracket 01B	34.75	0.04	180.0	0.0	34.00	18.00	2.00	--	3.00	0	364	364
Box	PANEL ANTENNA	34.00	12.21	0.0	0.0	30.86	23.62	6.26	--	11.93	-31	1,853	1,821
Box	Bracket 02A	34.00	6.08	0.0	0.0	34.00	12.00	2.00	--	3.00	-17	39	22
Box	PANEL ANTENNA	34.00	12.21	180.0	0.0	30.86	23.62	6.26	--	11.93	31	1,853	1,884
Box	Bracket 02A	34.00	6.08	180.0	0.0	34.00	12.00	2.00	--	3.00	17	39	57
Box	PANEL ANTENNA	34.00	12.21	270.0	0.0	30.86	23.62	6.26	--	11.93	1	972	973
Box	Bracket 02A	34.00	6.08	270.0	0.0	34.00	12.00	2.00	--	3.00	1	158	158
Cylinder	HL-44	32.33	0.32	0.0	0.0	25.00	66.00	--	7.00	--	1	1,794	1,794
Box	TRIPLEX	15.00	14.38	20.0	0.0	21.60	7.32	6.38	--	6.14	-25	112	87
Cylinder	Radio Mount 01	14.50	5.72	0.0	90.0	40.00	53.25	--	3.00	--	-19	239	220
Box	RRU UNIT	14.00	22.63	50.0	0.0	92.00	17.08	12.75	--	13.50	-116	515	399
Box	POWER BOX	14.00	18.20	85.0	0.0	22.20	12.99	3.89	--	11.42	-4	119	115
Box	RRU UNIT	14.00	22.63	310.0	0.0	92.00	17.08	12.75	--	13.50	-106	514	408

Box	POWER BOX	14.00	18.20	280.0	0.0	22.20	12.99	3.89	--	11.42	-5	122	117		
Cylinder	Radio Mount 01	14.00	5.75	0.0	90.0	40.00	53.25	--	3.00	--	-19	230	211		
Box	Fiber Box	Verizon	11.13	8.92	90.0	0.0	10.00	16.00	7.00	--	10.00	0	205	205	
Box	Breaker Box	Verizon	11.00	6.58	0.0	0.0	10.00	12.60	4.30	--	8.90	-5	203	198	
Box	Bracket 02A		34.00	6.08	90.0	0.0	34.00	12.00	2.00	--	3.00	-1	158	157	
Box	CBRS RADIO		34.00	11.54	90.0	0.0	11.02	8.40	4.92	--	7.90	0	272	271	
												Totals:	-298	11,519	11,221

Crossarm	Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)	
Offset	ALLEY ARM 3-1/2 X 4-1/2 X 6	28.88	5.63	90.0	90.0	40.00	5.50	4.50	96.00	159	135	295	
										Totals:	159	135	295

Streetlight	Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Height (in)	Unit Depth (in)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)	
General	Streetlight - 10 ft. Arm	22.38	3.76	180.0	180.0	85.00	24.00	20.00	3.00	120.00	631	1,692	2,323	
											Totals:	631	1,692	2,323

Insulator	Owner	Height (ft)	Horiz. Offset (in)	Offset Angle (deg)	Rotate Angle (deg)	Unit Weight (lbs)	Unit Diameter (in)	Unit Length (in)	Offset Moment* (ft-lb)	Wind Moment* (ft-lb)	Moment at GL* (ft-lb)		
Pin	Pin Insulator - 5 kV	29.10	88.00	176.3	0.0	6.00	3.50	7.50	0	91	91		
Pin	Pin Insulator - 5 kV	29.10	20.00	164.3	0.0	6.00	3.50	7.50	0	91	91		
Pin	Pin Insulator - 5 kV	29.10	50.00	173.6	0.0	6.00	3.50	7.50	0	91	91		
J-Hook	J-Hook	19.67	0.00	180.0	180.0	5.00	3.00	0.00	0	0	0		
J-Hook	J-Hook	24.92	0.00	0.0	0.0	5.00	3.00	0.00	0	0	0		
J-Hook	J-Hook	24.25	0.00	90.0	90.0	5.00	3.00	0.00	0	0	0		
J-Hook	J-Hook	18.92	0.00	90.0	90.0	5.00	3.00	0.00	0	0	0		
J-Hook	J-Hook	18.92	0.00	270.0	270.0	5.00	3.00	0.00	0	0	0		
										Totals:	0	272	272

Guy Wire and Brace	Owner	Attach Height (ft)	End Height (ft)	Lead/Span Length (ft)	Wire Diameter (in)	Percent Solid (%)	Lead Angle (deg)	Incline Angle (deg)	Wire Weight (lbs/ft)	Rest Length (ft)	Stretch Length (in)
EHS 1/2	Down	18.92	0.00	13.00	0.5	75.00	90.0	55.3	0.517	27.44	0.13

Guy Wire and Brace (Loads and Reactions)	Elastic Modulus (psi)	Rated Tensile Strength (lbs)	Guy Strength Factor	Allowable Tension (lbs)	Initial Tension (lbs)	Loaded Tension* ² (lbs)	Maximum Tension ² (lbs)	Applied Tension ³ (lbs)	Vertical Load (lbs)	Shear Load In Guy Dir (lbs)	Shear Load At Report Angle (lbs)	Moment at GL ³ (ft-lb)			
EHS 1/2	Down	2.30e+7	26,900	0.90	24,210	700	3,547	3,547	1,349	1,109	768	-29	-362		
											Totals:	1,109	767	-29	-362

Anchor/Rod Load Summary		Owner	Rod Length AGL (in)	Lead Length (ft)	Lead Angle (deg)	Strength of Assembly (lbs)	Anchor/Rod Strength Factor	Allowable Load (lbs)	Max Load ² (lbs)	Load at Pole MCU ³ (lbs)	Max Required Capacity ² (%)
Expanding - 12" - Soil Class 3			0.00	13.00	90.0	40,000	1.00	40,000	3,547	1,349	8.9

Pole Buckling

Buckling Constant	Buckling Column Height* (ft)	Buckling Section Height (% Buckling Col. Hgt.)	Buckling Section Diameter (in)	Minimum Buckling Diameter at GL (in)	Diameter at Tip (in)	Diameter at GL (in)	Modulus of Elasticity (psi)	Pole Density (pcf)	Ice Density (pcf)	Pole Tip Height (ft)	Buckling Load Capacity at Height (lbs)	Buckling Load Applied at Height (lbs)	Buckling Load Factor of Safety
0.71	20.94	33.62	9.32	3.72	6.69	10.15	2.13e+6	60.00	57.00	29.58	184,871	1859.52	55.56

POLE EXTENSION DESIGN

CONTROLLING DESIGN CODES

- 1) TIA-EIA-222-G (FOR WIND LOAD ON ANTENNAS AND ANTENNA SUPPORTING STRUCTURES)

DESIGN WIND PRESSURE

ELEVATION C/L ANTENNA: $E := 36.58\text{ft}$

BASIC WIND SPEED $V := 90\text{mph}$

EXPOSURE C

IMPORTANCE FACTOR $I := 1.0$

TOPOGRAPHIC FACTOR $K_{zt} := 1.0$

WIND DIRECTION FACTOR $K_d := 0.95$

GUST RESPONSE FACTOR STRUCTURE $G_h := 1.0$

$$K_z := 2.01 \cdot \left(\frac{E}{900\text{ft}} \right)^{\left(\frac{2}{9.5} \right)} = 1.02 \quad \text{Velocity Pressure Coefficient}$$

$$q_z := 0.00256 \cdot V^2 \cdot K_z \cdot K_{zt} \cdot K_d \cdot I \cdot \frac{\text{psf}}{\text{mph}^2} = 20.17 \cdot \text{psf}$$

EFFECTIVE WIND PRESSURE ON POLE STRUCTURE

$$p := \max(20\text{psf}, q_z \cdot G_h) = 20.17 \cdot \text{psf}$$

ANTENNA GROUP 1 LOADING

ANTENNA GROUP 1:

(3) PANEL ANTENNA (LARGEST ANTENNA)
(1) CANISTER ANTENNA
(1) CBRS RADIO

NUMBER OF FLAT ANT: $N1 := 4$

NUMBER OF ROUND ANT: $N1r := 1$

SIZE OF FLAT ANT: $H1 := \frac{(3 \cdot 24 + 1 \cdot 8.4)\text{in}}{N1} = 1.67 \text{ ft}$ $W1 := \frac{(3 \cdot 12 + 1 \cdot 7.9)\text{in}}{N1} = 0.91 \text{ ft}$

$D1 := \frac{(3 \cdot 6.5 + 1 \cdot 4.92)\text{in}}{N1r} = 2.04 \text{ ft}$

SIZE OF ROUND ANT: $H1r := \frac{(1 \cdot 24)\text{in}}{N1r} = 2 \text{ ft}$ $W1r := \frac{(1 \cdot 14.6)\text{in}}{N1r} = 1.22 \text{ ft}$

$D1r := \frac{(1 \cdot 14.6)\text{in}}{N1r} = 1.22 \text{ ft}$

WEIGHT OF ANTENNAS: $WT1_{\text{antenna}} := (3 \cdot 31 + 1 \cdot 11.02)\text{lb} = 104.02 \text{ lb}$

EFFECTIVE ANTENNA AREA $A1_{\text{ant.flat}} := 0.8N1 H1 \cdot W1$ $A1_{\text{ant.flat}} = 4.9 \text{ ft}^2$

$A1_{\text{ant.round}} := N1r H1r \cdot W1r$ $A1_{\text{ant.round}} = 2.43 \text{ ft}^2$

FORCE COEFFICIENTS PER TIA-222-G

Cf (ROUND MEMBER) $Cf_{\text{round}} := 1.2$ TIA-222-G, Tbl. 2-8a

Cf (FLAT MEMBER) $Cf_{\text{flat}} := 1.4$

ANTENNA GROUP 1 WIND LOAD $WL1_{\text{antenna}} := p \cdot (Cf_{\text{flat}} \cdot A1_{\text{ant.flat}} + Cf_{\text{round}} \cdot A1_{\text{ant.round}}) = 197.37 \text{ lb}$

$WL1_{\text{antenna}} = 197 \text{ lb}$

WEIGHT OF ANTENNAS: $WT1_{\text{antenna}} = 104.02 \text{ lb}$

ANTENNA CONNECTION TO EXTENSION POLE

WEIGHT OF 2" DIA. X 40" SCH 40 MOUNTING PIPE	WT _{pipe} := 15lb	Weight of (1) Pipe, (4) pipes considered
WOOD POLE TOP MOUNT WEIGHT	WT _{TMOUNT} := 40lb	(2) considered
U-BOLT & HARDWARE WEIGHT	WT _{hrdw} := 10lb	Weight of (1) Assembly, (6) considered
WEIGHT OF ANTENNA GROUP	WT _{ant.MAX} := WT _{1 antenna} + WT _{pipe} ·4 + WT _{hrdw} ·6 + WT _{TMOUNT} = 264.02 lb	
TOTAL LOAD IN CONNECTION TO POLE EXTENSION	$F_{conn} := \sqrt{WT_{ant.MAX}^2 + WL_{1 antenna}^2} = 329.64 \text{ lb}$	
5/8" DIA. THREADED FASTENER AVAILABLE TENSILE STRENGTH	R _{bt_allow} := 5.9kip	AISC ASD Manual, 9th Edition, Tbl. I-B
5/8" DIA. THREADED FASTENER AVAILABLE SHEAR STRENGTH	R _{bV_allow} := 3.1kip	AISC ASD Manual, 9th Edition, Tbl. I-D
	$IC := \frac{F_{conn}}{\min(R_{bt_allow}, R_{bV_allow})} = 0.11 < 1.0 \text{ OK}$	

EXTENSION POLE CHECK

HIGHLINE HL-44 OR APPROVED EQUIVALENT

WIND LOAD FROM ANTENNA
GROUP

$$WL1_{antenna} = 197 \text{ lb}$$

EQUIVALENT WIND LOAD FROM
ANTENNA AT 31 IN ABOVE EXTENSION
POLE CONNECTION

$$WL1_{antenna.eq} := \frac{68\text{in}}{31\text{in}} \cdot WL1_{antenna} = 432.94 \text{ lb} \quad < 1,000 \text{ lb OK}$$

THE HIGHLINE HL-44 EXTENSION POLE IS ADEQUATE TO TAKE THE LOAD PER
HIGHLINE PRODUCTS POLE TOP EXTENSION TESTING TEST #1 CANTILEVER TEST

EXTENSION POLE CONNECTION TO EXISTING POLE CHECK

Ca (EXTENSION POLE)

$$Cf_{round} = 1.2$$

EXTENSION POLE SIZE

$$HP := 72\text{in} \quad WP := 7.125\text{in}$$

EXTENSION POLE
EFFECTIVE AREA

$$A2_{pole} := Cf_{round} \cdot HP \cdot WP = 4.28 \text{ ft}^2$$

EXTENSION POLE WIND LOAD

$$F_{POLE} := p \cdot A2_{pole} = 86.25 \text{ lb}$$

3/4" DIA. THREADED FASTENER
AVAILABLE TENSILE STRENGTH

$$R_{bt_allow} := 8.4\text{kip} \quad \text{AISC ASD Manual, 9th Edition, Tbl. I-B}$$

3/4" DIA. THREADED FASTENER
AVAILABLE SHEAR STRENGTH

$$R_{bv_allow} := 8.8\text{kip} \quad \text{AISC ASD Manual, 9th Edition, Tbl. I-D}$$

$$d_1 := 84\text{in} \quad d_2 := 48\text{in} \quad d_3 := 8\text{in}$$

MOMENT IN CONNECTION

$$M_r := WL1_{antenna} \cdot (d_1) + F_{POLE} \cdot (d_2) = 1726.56 \text{ lb} \cdot \text{ft}$$

SHEAR/TENSION IN BOLTS

$$R_{TP} := \frac{M_r}{d_3} = 2589.84 \text{ lb}$$

TOTAL SHEAR PER BOLT

$$V_{max} := R_{TP} = 2589.84 \text{ lb}$$

$$IC_v := \frac{V_{max}}{R_{bv_allow}} = 0.29 \quad < 1.0 \text{ OK}$$

BOLTS AVAILABLE SHEAR
STRENGTH FOR SAWN LUMBER

$$Z_{perp} := 1.6 \cdot 2000\text{lb} = 3200 \text{ lb}$$

$$IC := \frac{V_{max}}{\min(R_{bv_allow}, Z_{perp})} = 0.81 \quad < 1.0 \text{ OK}$$

ADDITIONAL EQUIPMENT FIBER BOX AND BREAKER BOX

ADDITIONAL EQUIPMENT: (1) FIBER ENCLOSURE
(1) BREAKER BOX

NUMBER OF EQ: $N3 := 2$

SIZE OF EQ: $H3 := \frac{(1 \cdot 12.6 + 1 \cdot 12.13)}{N3} \text{in}$ $W3 := \frac{(1 \cdot 8.9 + 1 \cdot 12.13)}{N3} \text{in}$

WEIGHT OF RF EQ: $WT3_{\text{antenna}} := (1 \cdot 10 + 1 \cdot 10) \text{lb}$

EFFECTIVE EQUIPMENT AREA $A3_{\text{antenna}} := H3 \cdot W3 \cdot N3$ $A3_{\text{antenna}} = 1.81 \text{ ft}^2$

ADNL EQUIPMENT WIND LOAD $WL3_{\text{antenna}} := p \cdot Cf_{\text{flat}} \cdot A3_{\text{antenna}}$ $WL3_{\text{antenna}} = 51 \text{ lb}$

TOTAL WEIGHT OF ADTL EQUIPMENT $WT_{\text{adtl}} := WT3_{\text{antenna}} + 2 \cdot 20 \text{lb} = 60 \text{ lb}$

TOTAL WIND LOAD ON ADTL EQUIPMENT $WL_{\text{adtl}} := WL3_{\text{antenna}} = 51 \text{ lb}$

TOTAL LOAD IN CONNECTION TO EXISTING POLE $F_{\text{conn}} := \sqrt{WT_{\text{adtl}}^2 + WL_{\text{adtl}}^2} = 78.75 \text{ lb}$

TOTAL SHEAR PER BOLT $V_{\text{max}} := F_{\text{conn}} \cdot 0.5 = 39.37 \text{ lb}$

5/8" DIA. THREADED FASTENER AVAILABLE TENSILE STRENGTH $R_{bt_allow} := 5.9 \text{ kip}$ AISC ASD Manual, 9th Edition, Tbl. I-B

5/8" DIA. THREADED FASTENER AVAILABLE SHEAR STRENGTH $R_{bv_allow} := 3.1 \text{ kip}$ AISC ASD Manual, 9th Edition, Tbl. I-D

BOLTS AVAILABLE SHEAR STRENGTH FOR SAWN LUMBER $Z_{\text{perp}} := 1.6 \cdot 760 \text{lb} = 1216 \text{ lb}$

$IC := \frac{V_{\text{max}}}{\min(R_{bv_allow}, Z_{\text{perp}})} = 0.03 < 1.0 \text{ OK}$

RRU MOUNT CONNECTION TO NEW WOODEN UTILITY POLE

ANTENNA GROUP 4

(2) RADIO UNITS, (1) DIPLEXER, (2) POWER UNITS

NUMBER OF ANT:

$$N4 := 5$$

SIZE OF ANT:

$$H4 := \frac{(2 \cdot 17.1 + 1 \cdot 6.4 + 2 \cdot 13) \text{in}}{N4} = 1.11 \text{ ft}$$

$$W4 := \frac{(2 \cdot 13.5 + 1 \cdot 7.32 + 2 \cdot 11.42) \text{in}}{N4} = 0.95 \text{ ft}$$

$$D4 := \frac{(2 \cdot 12.75 + 1 \cdot 6.14 + 2 \cdot 3.89) \text{in}}{N4} = 0.66 \text{ ft}$$

WEIGHT OF ANTENNAS:

$$WT_{4\text{ antenna}} := [2 \cdot (72 + 10) + 1 \cdot 15.2 + 2 \cdot 22.1] \text{lb} = 223.4 \text{ lb}$$

EFFECTIVE ANTENNA AREA

$$A4_{\text{antenna}} := N4 \cdot (H4 \cdot W4) \quad A4_{\text{antenna}} = 5.29 \text{ ft}^2$$

ANTENNA GROUP 4 WIND LOAD

$$WL_{4\text{ antenna}} := p \cdot C_{f\text{ flat}} \cdot A4_{\text{antenna}}$$

$$WL_{4\text{ antenna}} = 149 \text{ lb}$$

WEIGHT OF ANTENNAS:

$$WT_{4\text{ antenna}} = 223.4 \text{ lb}$$

WEIGHT OF 2" DIA. X 30" SCH 40
MOUNTING PIPE

$$WT_{\text{pipe2}} := 10 \text{lb} \quad \text{Weight of (1) Pipe, (2) pipes considered}$$

WEIGHT OF 2 3/8" DIA. X 24" SCH 40
MOUNTING PIPE

$$WT_{\text{pipe2.3}} := 7.5 \text{lb} \quad \text{Weight of (1) Pipe, (2) pipes considered}$$

WEIGHT OF 3" X 3" X3/8" X 53.25"
LONG TUBE

$$WT_{\text{TUBE}} := 33 \text{lb} \quad \text{Weight of (1) Tube, (2) tubes considered}$$

BRACKETS WEIGHT

$$WT_{\text{bracket}} := 20 \text{lb} \quad \text{Weight of (1) Bracket, (8) Brackets considered}$$

WEIGHT OF ANTENNA GROUP

$$WT_{\text{ant.MAX}} := WT_{4\text{ antenna}} + WT_{\text{pipe2}} \cdot 2 + 2WT_{\text{TUBE}} + 2WT_{\text{pipe2.3}} \dots = 484.4 \text{ lb} \\ + WT_{\text{bracket}} \cdot 8$$

TOTAL LOAD IN CONNECTION TO
POLE

$$F_{\text{conn}} := \sqrt{WT_{\text{ant.MAX}}^2 + WL_{4\text{ antenna}}^2} = 506.9 \text{ lb}$$

5/8" DIA. THREADED FASTENER
AVAILABLE TENSILE STRENGTH

$R_{bt_allow} := 5.9\text{kip}$ AISC ASD Manual, 9th Edition, Tbl. I-B

5/8" DIA. THREADED FASTENER
AVAILABLE SHEAR STRENGTH

$R_{bV_allow} := 3.1\text{kip}$ AISC ASD Manual, 9th Edition, Tbl. I-D

$$IC := \frac{F_{conn}}{\min(R_{bt_allow}, R_{bV_allow})} = 0.16 < 1.0 \text{ OK}$$

$$d_1 := \frac{53.25\text{in}}{2} = 2.22 \text{ ft}$$

Antenna Center Line to Bracket Attachment Center

$$d_2 := 19.5\text{in}$$

Distance between Bracket Bolts

MOMENT IN CONNECTION

$$M_r := WL4_{antenna} \cdot (d_1) = 331.34 \text{ lb}\cdot\text{ft}$$

SHEAR/TENSION IN BOLTS

$$R_{TP} := \frac{M_r}{d_2} = 203.9 \text{ lb}$$


TOTAL SHEAR PER BOLT


$$V_{max} := \sqrt{R_{TP}^2 + WL4_{antenna}^2} = 252.74 \text{ lb}$$

BOLTS AVAILABLE SHEAR
STRENGTH FOR SAWN LUMBER



$$Z_{perp} := 1.6 \cdot 760\text{lb} = 1216 \text{ lb}$$

$$IC := \frac{V_{max}}{\min(R_{bV_allow}, Z_{perp})} = 0.21 < 1.0 \text{ OK}$$





RADIOS W/INTEGRATED ANTENNAS & CBRS RADIO TYPICAL MOUNTING DETAIL (PLAN VIEW)



SIDE-BY-SIDE RRU MOUNT CONNECTION

BOLTS

**Table 12B BOLTS: Reference Lateral Design Values, Z, for Single Shear
(two member) Connections^{1,2}**

for sawn lumber or SCL main member with 1/4" ASTM A 36 steel side plate

Thickness t_{in}	Main Member t_{in}	Side Member t_{in}	Bolt Diameter D in.	G=0.67 Red Oak		G=0.55 Mixed Maple Southern Pine		G=0.50 Douglas Fir-Larch		G=0.49 Douglas Fir-Larch(N)		G=0.46 Douglas Fir(FirS) Hem-Fir(N)		G=0.43 Hem-Fir		G=0.42 Spruce-Pine-Fir		G=0.37 Redwood (open grain)		G=0.36 Eastern Softwoods Spruce-Pine-Fir(S)		G=0.35 Western Cedars Western Woods		Northern Species	
				Z_{II} lbs.	Z_{I} lbs.	Z_{II} lbs.	Z_{I} lbs.	Z_{II} lbs.	Z_{I} lbs.	Z_{II} lbs.	Z_{I} lbs.	Z_{II} lbs.	Z_{I} lbs.	Z_{II} lbs.	Z_{I} lbs.	Z_{II} lbs.	Z_{I} lbs.	Z_{II} lbs.	Z_{I} lbs.	Z_{II} lbs.	Z_{I} lbs.	Z_{II} lbs.	Z_{I} lbs.		
				1/2	730	420	620	350	580	310	580	310	550	290	520	280	510	270	470	240	460	240	450	230	
1-1/2	1/4	1/4	1/2	730	420	620	350	580	310	580	310	550	290	520	280	510	270	470	240	460	240	450	230		
			5/8	910	480	780	400	730	360	720	360	690	340	650	320	640	320	590	290	580	280	560	270		
			3/4	1090	550	940	450	870	420	860	410	820	390	780	360	770	360	710	320	690	320	680	310		
			7/8	1270	600	1090	510	1020	470	1010	450	960	430	910	410	900	400	820	370	810	360	790	350		
			1	1460	660	1250	550	1170	510	1150	500	1100	480	1040	450	1030	450	940	400	930	400	900	390		
1-3/4	1/4	1/4	1/2	810	460	690	370	640	340	630	330	600	310	570	290	560	280	510	250	500	250	490	240		
			5/8	1020	520	870	430	800	390	790	380	750	360	710	340	700	330	640	300	630	290	610	280		
			3/4	1220	590	1040	480	960	440	950	430	900	410	860	380	840	370	770	330	750	330	730	320		
			7/8	1420	650	1210	540	1130	490	1110	480	1050	450	1000	420	980	420	890	380	880	370	850	360		
			1	1630	710	1380	580	1290	540	1270	520	1200	500	1140	470	1120	460	1020	410	1000	410	980	400		
2-1/2	1/4	1/4	1/2	930	600	860	470	830	410	820	400	780	380	740	350	720	340	650	300	640	290	620	280		
			5/8	1370	670	1150	530	1050	470	1040	470	980	430	920	400	910	390	810	340	800	330	770	320		
			3/4	1640	750	1370	590	1270	530	1250	520	1180	490	1110	450	1090	440	980	380	960	370	930	360		
			7/8	1910	820	1600	650	1480	590	1450	570	1370	530	1290	490	1270	480	1140	420	1120	410	1080	400		
			1	2190	880	1830	700	1690	640	1660	620	1570	580	1480	540	1450	530	1300	460	1280	450	1240	440		
3-1/2	1/4	1/4	1/2	930	620	860	550	830	510	820	510	800	480	770	450	770	430	720	370	720	360	710	350		
			5/8	1370	860	1260	760	1210	710	1200	700	1160	670	1130	640	1120	630	1060	580	1050	560	1030	540		
			3/4	1900	990	1740	760	1670	680	1660	660	1580	610	1480	560	1450	540	1290	460	1260	450	1220	440		
			7/8	2530	1070	2170	840	1990	740	1950	710	1840	660	1720	610	1690	590	1510	510	1480	500	1430	470		
			1	2980	1150	2480	890	2270	800	2230	770	2100	730	1970	660	1930	650	1720	560	1690	540	1630	530		
5-1/4	1/4	1/4	5/8	1370	860	1260	760	1210	710	1200	700	1160	670	1130	640	1120	630	1060	580	1050	560	1030	540		
			3/4	1900	1140	1740	1000	1670	940	1660	930	1610	860	1560	770	1550	760	1460	640	1450	620	1420	600		
			7/8	2530	1460	2320	1150	2220	1050	2200	1010	2140	920	2070	840	2050	820	1940	700	1920	680	1890	640		
			1	3260	1660	2980	1270	2860	1130	2840	1080	2750	1010	2670	920	2640	890	2490	750	2450	730	2360	710		
5-1/2	1/4	1/4	5/8	1370	860	1260	760	1210	710	1200	700	1160	670	1130	640	1120	630	1060	580	1050	570	1030	560		
			3/4	1900	1140	1740	1000	1670	940	1660	930	1610	890	1560	850	1550	840	1460	760	1450	750	1420	740		
			7/8	2530	1460	2320	1240	2220	1090	2200	1050	2140	960	2070	880	2050	860	1940	730	1920	710	1890	660		
			1	3260	1730	2980	1320	2860	1170	2840	1130	2750	1050	2670	950	2640	930	2490	780	2470	760	2420	740		
7-1/2	1/4	1/4	5/8	1370	860	1260	760	1210	710	1200	700	1160	670	1130	640	1120	630	1060	580	1050	570	1030	560		
			3/4	1900	1140	1740	1000	1670	940	1660	930	1610	890	1560	850	1550	840	1460	760	1450	750	1420	740		
			7/8	2530	1460	2320	1280	2220	1210	2200	1180	2140	1130	2070	1080	2050	1070	1940	960	1920	930	1890	870		
9-1/2	1/4	1/4	3/4	1900	1140	1740	1000	1670	940	1660	930	1610	890	1560	850	1550	840	1460	760	1450	750	1420	740		
			7/8	2530	1460	2320	1280	2220	1210	2200	1180	2140	1130	2070	1080	2050	1070	1940	960	1920	970	1890	930		
			1	3260	1820	2980	1590	2860	1500	2840	1470	2750	1420	2670	1350	2640	1330	2490	1220	2470	1200	2420	1180		
11-1/2	1/4	1/4	7/8	2530	1460	2320	1280	2220	1210	2200	1180	2140	1130	2070	1080	2050	1070	1940	980	1920	970	1890	930		
			1	3260	1820	2980	1590	2860	1500	2840	1470	2750	1420	2670	1350	2640	1330	2490	1220	2470	1200	2420	1180		
13-1/2	1/4	1/4	7/8	2530	1460	2320	1280	2220	1210	2200	1180	2140	1130	2070	1080	2050	1070	1940	980	1920	970	1890	930		
			1	3260	1820	2980	1590	2860	1500	2840	1470	2750	1420	2670	1350	2640	1330	2490	1220	2470	1200	2420	1180		

1. Tabulated lateral design values, Z, for bolted connections shall be multiplied by all applicable adjustment factors (see Table 11.3.1).
 2. Tabulated lateral design values, Z, are for "full-body diameter" bolts (see Appendix Table L1) with bolt bending yield strength, F_y , of 45,000 psi and dowel bearing strength, F_u , of 87,000 psi for ASTM A36 steel.

HL-44 Fiberglass Pole Top Extensions

PRODUCT FEATURES

- Reduces costs.
 - Pole top extension installation costs are much less than the removal and replacement of existing pole.
 - The installation of a pole top reduces the number of personnel and amount of equipment needed to remove a pole.
 - Existing wiring and top equipment can be left untouched.
- Holes drilled to customer specifications.
- State of the art manufacturing technology.
- Stronger than the pole.
- Tens of thousands in service.
- Wide variety of brackets available.
- Excellent weatherability, UV protected.




Pole Top Extensions

Tube Sketch



Bracket Sketch



Comes in standard brown.

CUSTOMER NAME

Tube & Bracket Specifications

All pole top extensions are customer specific—please check boxes for each specification needed.

1. **Length:** Standard is 54"
 54" 36" 48" 60" 72" 92" 120" Other _____
2. **Drilled Holes In Tube:** Standard hole diameter is 11/16", other diameters are available at extra cost
 No Holes in Tube Other (mark above tube sketch with hole position dimensions)
3. **Bracket Style:** Standard is B bracket. Additional styles available.
 6"-12" Diameter poles (B bracket) 6 1/2" - 9" Diameter poles (A bracket)
4. **Cap Type:**
 Plain Molded in nut 3/4" Ridge pin 3/4"


Comments: _____

Highline Products Pole Top Extension Testing

Highline Products has been manufacturing and selling Pole-Top extension for over 40 years. The following results are from testing preformed by various Electric Utilities.

Test #1 Cantilever Pull Test

54" Pole Top Extension with a force applied 31" from the bottom of the pole top and the force parallel to the conductors. Deflection measurements were taken.



Lbs.	Deflection
200	0.000"
500	.354"
1000	.679"
1500	.989"
2000	1.294"
2500	1.594"
3000	1.889"
3500	2.179"
4000	2.399"
4500	2.849"
4900	3.629"


Comments: The pole top hold down in line with the force failed by shear at 4900 pounds. Initial composite crackling was heard at 2500 pounds but no damage to the pole top was detected after the test.

Test #2- Crossarm- Cantilever torsion

54" Poletop Extension with a 8ft Crossarm mounted 40" above mounting brace. Force was applied at the end of the Crossarm, where dead end insulator would be mounted, 42" from pole centerline. Deflection measurements were taken of the crossarm.


Lbs.	Deflection
100	0.000"
200	8.000"
300	14.000"
400	19.590"
500	21.000"

Comments: The 8ft cross arm bolting and braces bent during this torsional test with no detectable deflection of the pole top extension and no permanent deformation in the support bracket.




Test #3- Shear test on bolt holes

An 8,000kg (17,637 lbs) load was applied to 5/8" thru bolt pass through pole top extension. No significant damage noticed, just minor scratches.



Test #4- Guying

A 54" pole top extension was tested using (2) standard guy fixtures on opposite sides of the extension. A load of 15,000 lbs was applied on each guy fixture. No hole elongation or damage was noted to the fiberglass, but there was noticeable bending to bolts.



Over the past 40 years Highline Products has sold thousands of Pole Top Extensions with no known failures or issues. Generally, the pole top extension is stronger than the mounting equipment.

The fiberglass tube manufactured by Highline is circularly wound using high-grade fiberglass and epoxy resin for superior strength and durability. Black carbon pigment is added to for additional UV protection. The outer surface has a minimum of 10mils of resin and is then painted with a high quality polyurethane paint. This combination offers the best protection available against the elements and results in a superior looking product.

LIMITATIONS

The recommendations contained within this report were developed using general project information provided by the owner, manufacturer, general field observations, reference information and laboratory testing data, as applicable. All recommendations pertain only to the proposed structure construction, location, and loading as described in this report. Concordia Wireless assumes no responsibility for failures caused by factors beyond our control. These include but are not limited to the following:

1. Missing, corroding, and/or deteriorating members
2. Improper manufacturing and/or construction
3. Improper maintenance

Concordia Wireless assumes no responsibility for modifications completed prior to or hereafter in which Concordia Wireless was not directly involved. These modifications include but are not limited to the following:

1. Replacing or strengthening bracing members
2. Reinforcing or extending vertical members
3. Installing or removing antenna mounting gates or side arms
4. Changing loading configurations

Furthermore, Concordia Wireless hereby states that this document represents the entire report and that it assumes no liability for any factual changes that may occur after the date of this report. All representations, recommendations and conclusions are based on the information contained and set forth herein. If you are aware of any information contrary to that contained herein, or if you are aware of any defects arising from the original design, material, fabrication and erection deficiencies, you should disregard this report and immediately contact Concordia Wireless. Concordia Wireless isn't liable for any representation, recommendation or conclusion not expressly stated herein.



1515 E Woodfield Rd
Suite 1000
Schaumburg, IL 60173

July 10, 2020

Village of Clarendon Hills
One North Prospect Avenue
Clarendon Hills, Illinois 60514

**Re: Certification Letter to The Village of Clarendon Hills Ordinance No. 18-07-20
Proposed Verizon Wireless Small Wireless Facility Collocation
Project Name: WINDSOR & EAST
Location ID: 456606
Address: 3200 East Ave, Berwyn IL 60402**

To Whom It May Concern:

This Letter serves as certification that to the best of Verizon Wireless' knowledge, the proposed small wireless facility collocation complies with all the requirements, including the written design standards, as set forth by The Village of Clarendon Hills Ordinance No. 18-07-20.


Should you have any additional questions or concerns, please contact me at (847) 706-7600.

Thank you for your attention to this matter.

Sincerely,


Edward Rios
Verizon Wireless
Engineer III Specialist - Real Estate/Regulatory

STREET MAP ATTACHMENT



**From 1 North Prospect Ave
to 1 Arthur Ave, Clarendon Hills, IL 60514**

AERIAL PHOTO ATTACHMENT



SITE PHOTOS



View of Utility Pole (Looking Northwest)

SITE PHOTOS



View of Utility Pole (Looking Northeast)

SITE PHOTOS



View of Utility Pole (Looking Southeast)

SITE PHOTOS



View of Utility Pole (Closeup view)